



**Contents :**

- |   |              |
|---|--------------|
| <b>The Hybrid Eco Vehicles (H.E.V), the Future of Indian Transport</b><br>Vaibhav Dixit, Sachin Mishra, Sourav Sharma, Shiersh Pandey   | <b>01-03</b> |
| <b>Effect of Fly ash on Strength Characteristics of Roller Compacted Concrete Pavement</b><br>S.Pavan, S. Krishna Rao   | <b>04-08</b> |
| <b>Experimental Investigation of Buckling of Laminated Composite Cylindrical Shells with &amp;Without Cutouts Subjected To Axial Compression</b><br>Anil Kumar Nagari, Venkata Narayana Yenugula                | <b>09-14</b> |
| <b>A Study to Replace Existing Causeway to Bridge at Sathy - Periyakodiveri- Kadambur Road</b><br>Loganayagan.S, Mahesh. V, Karthiga @ Shenbagam.N, Ramesh. A. S, Chandra Mohan.N                               | <b>15-24</b> |
| <b>Effect of Flow Condition and Base Contact Ratio of Perfor-ated Array Fins on Heat Transfer Augmentation using Computational Fluid Dynamics technique</b><br>Ankit Vyas, Prof Sunil Gupta, Prof Sandeep Gupta | <b>25-30</b> |
| <b>Study of Queuing System of a Busy Restaurant and a Proposed Facilitate Queuing System</b><br>Md. Manjurul Ahsan, Md. Raisul Islam, Md. Ashikul Alam  | <b>31-35</b> |
| <b>Evaluation of Adequacy Fishery Port Infrastructure (Case Study on Fishery Port Mimbo Situbondo)</b><br>Noor Salim  | <b>36-46</b> |
| <b>Homogeneous Charge Compression Ignition (HCCI) Combustion Engine- A Review</b><br>Pravin Kumar, A. Rehman  | <b>47-67</b> |

## *IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE)*

### **Managing Editor Board**

- ❖ Dr. S.Prakash  
Sathyabama University, India
- ❖ Dr. Idris, Musibaudeen Olatunde  
The Federal Polytechnic Ede, Osun State, Nigeria
- ❖ Dr. Salah Hamed Ramadan Ali  
National Institute for Satandards (NIS), Egypt
- ❖ Dr. Mohammad Valipour  
University of Tehran, Iran
- ❖ Dr. Abdul Latif Qureshi  
Mehran Univ. of Engg. & Tech., Jamshoro, Pakistan
- ❖ Dr. Trouzine Habib  
LGCE, Sidi Bel Abbes University, Algeria

### **International Editorial Board**

- ❖ Dr. Said Abdel-Aleem Farag Hawash  
National Water Research Center (NWRC), Egypt
- ❖ Dr. S. K. Mangal  
PEC Univerisity of Technology, India
- ❖ Dr. Rajeshkumar U. Sambhe  
Sant Gadge Baba Amravati University, Amravati, India
- ❖ Dr. Aginam, Chukwurah Henry  
Nnamdi Azikiwe University Awka, Anambra Nigeria
- ❖ Dr. Pramod Kumar Gupta  
IIT Roorkee, India
- ❖ Dr. P.Sivaprakash  
Karpagam Institute of Technology, India

### **IOSR Journals subscription**

Institute or any person can subscribe the hard copy of IOSR Journals. All subscription are payable in advance. Journals are sent by air to all countries except Indian subcontinent. Subscriptions are on annual basis. For more detail of subscription, log on to [www.iosrjournals.org](http://www.iosrjournals.org)

### **Contact Us**

Website URL : [www.iosrjournals.org](http://www.iosrjournals.org)

Email : [iosrjmce@gmail.com](mailto:iosrjmce@gmail.com)

#### **Qatar Office:**

IOSR Journals  
Salwa Road  
Near to KFC and Aziz  
Petrol Station,  
DOHA, Qatar

#### **India Office:**

IOSR Journals  
SC-89 A, Shastri Nagar,  
Ghaziabad, UP,  
India

#### **Australia Office:**

43, Ring Road,  
Richmond Vic 3121  
Australia

#### **New York Office:**

8th floor, Straight hub,  
NS Road, New York,  
NY 10003-9595

### Submit your paper in IOSR Journals

Submissions must be original and should not have been published previously or be under consideration for publication while being evaluated by IOSR Journals. All articles are requested to submit their articles in M.S Word format to online submission process on IOSR Journals website [www.iosrjournals.org](http://www.iosrjournals.org)

### Terms of Submission

Papers must be submitted on the understanding that they have not been published elsewhere and are not currently under consideration by another journal. The submitting author is responsible for ensuring that the article's publication has been approved by all the other coauthors. It is also the authors' responsibility to ensure that the articles emanating from a particular institution are submitted with the approval of the necessary institution. Only an acknowledgment from the editorial office officially establishes the date of receipt. Further correspondence and proofs will be sent to the principal author before publication unless otherwise indicated. It is a condition of submission of a paper that the authors permit editing of the paper for readability.

### Blind Peer Review

All manuscripts are subject to blind peer review and are expected to meet standards of academic excellence. Submissions will be considered by an associate editor and if not rejected right away by peer-reviewers, whose identities will remain anonymous to the authors.

### Paper Acceptance:

The final decision on publication is made by the Editor-in-Chief upon recommendation of the Editorial Board Members. If the manuscript is accepted for publication, it must not be published in any periodicals elsewhere without the permission of the editorial board

### Copyright Form

Open Access authors retain the copyrights of their papers, and all open access articles are distributed under the terms of the Creative Commons Attribution license, which permits unrestricted use, distribution and reproduction in any medium, provided that the original work is properly cited.

The use of general descriptive names, trade names, trademarks, and so forth in this publication, even if not specifically identified, does not imply that these names are not protected by the relevant laws and Regulations.

While the advice and information in this journal are believed to be true and accurate on the date of its going to press, neither the authors, the editors, nor the publisher can accept any legal responsibility for Any errors or omissions that may be made. The publisher makes no warranty, express or implied, with Respect to the material contained herein.

### IOSR Journals Indexing Partners

All published paper in IOSR Journals index in following world wide libraries.





**Contents :**

|   |       |
|---|-------|
| The Hybrid Eco Vehicles (H.E.V), the Future of Indian Transport<br>Vaibhav Dixit, Sachin Mishra, Sourav Sharma, Shiersh Pandey  | 01-03 |
| Effect of Fly ash on Strength Characteristics of Roller Compacted Concrete Pavement<br>S.Pavan, S. Krishna Rao  | 04-08 |
| Experimental Investigation of Buckling of Laminated Composite Cylindrical Shells with & Without Cutouts Subjected To Axial Compression<br>Anil Kumar Nagari, Venkata Narayana Yenugula                  | 09-14 |
| A Study to Replace Existing Causeway to Bridge at Sathy - Periyakodiveri- Kadambur Road<br>Loganayagan.S, Mahesh. V, Karthiga @ Shenbagam.N, Ramesh. A. S, Chandra Mohan.N                              | 15-24 |
| Effect of Flow Condition and Base Contact Ratio of Perforated Array Fins on Heat Transfer Augmentation using Computational Fluid Dynamics technique<br>Ankit Vyas, Prof Sunil Gupta, Prof Sandeep Gupta | 25-30 |
| Study of Queuing System of a Busy Restaurant and a Proposed Facilitate Queuing System<br>Md. Manjurul Ahsan, Md. Raisul Islam, Md. Ashikul Alam   | 31-35 |
| Evaluation of Adequacy Fishery Port Infrastructure (Case Study on Fishery Port Mimbo Situbondo)<br>Noor Salim   | 36-46 |
| Homogeneous Charge Compression Ignition (HCCI) Combustion Engine- A Review<br>Pravin Kumar, A. Rehman   | 47-67 |

### About IOSR :

**International Organization of Scientific Research (IOSR)** is a registered independent Organization, a unit of CS delivering supports and services to education professionals and researchers around world, especially those from developing countries.

**IOSR** is the association of Scientists, Research scholars, Professors, Directors, Managers, Engineers, Pharma persons of various fields like Engineering, Management, Pharmacy, Applied Science, and Mathematics.

**IOSR** helps the researchers free of cost by providing right direction in their research with the help of its worldwide research association members.

### About IOSR Journals

**IOSR Journals** a broad-based open access, was founded on two key tenets: To publish the most exciting research with respect to the subjects of our functional Journals. Secondly, to provide a rapid turn-around time possible reviewing and publishing, and and to disseminate the articles freely for teaching...

### IOSR Journals Achievements

Today, the **IOSR Journals** is becoming a major international research journal editors and thesis research. We acquire, develop, market and distribute the knowledge through the dissemination of academics and practitioners from around the world. All journals published by us maintain the...

### IOSR Journals Mission

Our mission is to contribute to the progress and application of scientific discoveries, by providing free access to research information online without financial, legal or technical barriers. All International...

### IOSR Journals Values

At **IOSR Journals** we have a clear set of values for delivering our vision. These are:

\* Research Orientation \* Valuing Our Users \* Quality Control \* Innovation....

### LIST OF JOURNALS :

- IOSR Journal of Computer Engineering (IOSR-JCE)
- IOSR Journal of Electrical and Electronics Engineering (IOSR-JEEE)
- IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE)
- IOSR Journal of Electronics and Communication Engineering (IOSR-JECE)
- IOSR Journal of VLSI and Signal Processing (IOSR-JVSP)
- IOSR Journal of Environmental Science, Toxicology and Food Technology (IOSR-JESTFT)
- IOSR Journal of Humanities and Social Science (IOSR-JHSS)
- IOSR Journal of Pharmacy and Biological Science (IOSR-JPBS)
- IOSR Journal of Business and Management (IOSR-JBM)
- IOSR Journal of Dental and Medical Sciences (IOSR-JDMS)
- IOSR Journal of Agriculture and Veterinary Science (IOSR-JAVS)
- IOSR Journal of Applied Physics (IOSR-JAP)
- IOSR journal of Applied Chemistry (IOSR-JAC)
- IOSR Journal of Mathematics (IOSR-JM)
- IOSR Journal of Research & Method in Education (IOSR-JRME)
- IOSR Journal of Applied Geology and Geophysics (IOSR-JAGG)
- IOSR Journal of Nursing and health Science (IOSR-JNHS)
- IOSR Journal of Economics and Finance (IOSR-JEF)
- IOSR Journal of Sports and Physical Education (IOSR-JSPE)
- IOSR Journal of Polymer and Textile Engineering (IOSR-JPTE)
- IOSR Journal of Mobile Computing & Application (IOSR-JMCA)

## **Evaluation of Adequacy Fishery Port Infrastructure (Case Study on Fishery Port Mimbo Situbondo)**

Noor Salim

*Faculty of Technic, Muhammadiyah University of Jember*

---

**Abstract:** Fishery Port City Beach is located in the district of Situbondo Banyu Putih which is approximately 50 km from the city center. Exact location of the fishery port in the district directly adjacent to the Banyu Putih Banyuwangi industrial plant which contained fish canning factory in the district Muncar. In development, this port functions not only as a fishery port but also, as the crossing place to the Sepudi island which is included of Madura district. Different from the original plan, transportation within the port has changed. Reserved parking area no longer function optimally. So that needs to be addressed and the need for further study are: to analyze the adequacy of the pier and parking lot, and to evaluate the adequacy of the road in the hinterland. From the results, we get few things: The need for the loading dock and mooring for a boat the size of the existing less or more than 10 GT still be fulfilled properly. Unloading dock for ship size is less or more than 10 GT still be met but overload jetty mooring for vessels up to 254% for vessel with size of more than 10 GT and 128% for vessels less than 10 GT size. By changing the way the mooring of vessels dilated / transverse require less space, so the ship mooring space requirements can be fulfilled until 2016. The adequacy of existing parking space is available for cars and trucks only and can provide for parking requirement. The number of vehicles entering the port increased so that parking spaces be overloaded so it is need to provide parking spaces for motorcycles and pick-up. By utilizing the tip of the breakwater area for motorcycle parking space (688 m<sup>2</sup>) with a pattern of two sides and the base of the breakwater area for car parking (650m<sup>2</sup>) with a pattern of one side and a parking area that has been available previously for the truck and pick-up, parking space requirements can be fulfilled. Adequacy Road at Hinterland area with increasing number of vehicles in 2016, so the level of service drops to C but still decent. By widening the ring road towards Situbondo according to standard (7 m), it can be an alternative for heavy vehicles which go to Situbondo.

**Keywords:** Adequacy evaluations, docks, parking, street

---

### **I. Introduction**

Geographically, Situbondo City Region is located directly adjacent to the east side of the ocean that is the Madura Strait, therefore the majority of the population domiciled and do their activity near the beach or coastal region in addition to the City of Situbondo.

Fishery Port City Beach is located in the district of Situbondo Banyu Putih which is approximately 50 km from the city center. Exact location of the fishery port in the district the Banyu Putih directly adjacent to Banyuwangi industrial plant which contained fish canning factory in the district Muncar.

In the development of this port functions not only as a fishery port but also as the place crossing to the Sepudi island which is included of Madura district. Different from the original plan, transportation within the port has changed. Reserved parking area no longer function optimally. The visitors who came to trade prefer to park their vehicle not far from where they were. So if they take place in or on the side of the breakwater pier, they park their vehicles there as well as the location because distance of the parking area and a desirable place is too far.

Fishery port in carrying out various activities should be equipped with the dock, which is consist of unloading dock, mooring docks, and dock supplies. These facilities must have to support each other so that it will launch all activities that occur in the fishery port.

Under the circumstances, there are several problems need attention and need to be further investigated, namely: to analyze the adequacy of the pier and parking lot, and to evaluate the adequacy of the road in the hinterland area.

### **II. Research Methodology**

Operational scheme of research conducted to assess the transportation management of fishing ports are presented in the following chart.




Figure 1. Framework of Operational Research

**Research Location**

The research was conducted in coastal fisheries the Port City of Situbondo and in the hinterland traffic, in this intersection a four-stroke without signal as sample.

**Secondary Data**

Secondary data include:

1. Ships trends data, obtained from Fishery Port Manager Unit of Mimbo Beach.
2. Vehicles trends data, obtained from the Central Statistics Agency of Situbondo City.

**Primary Data**

Primary data were obtained by direct observation include:

1. The number of vehicles in and out of the port data
2. Traffic volume at the intersection of four junction in hinterland area data

**Data Collection**

In addition to the secondary data obtained from the SitubondoFishery PortBeach Manager Unit, Situbondo Statistics Center, and the data from the department of marine and coastal fishing town of Situbondo, conducted a survey to obtain primary data on the number of vehicles in and out of the port and the characteristics of traffic in hinterland area. In the survey, there are several qualifications to the data collection process which can be seen in the following table.

Table 1. Qualification data collection process

| Number | Qualifications                        | Exit-entry fishery port  | Not signalized intersection of four  |
|--------|---------------------------------------|--|--|
| 1      | Surveyor which involved in the survey | Surveyor involved in the survey required is 4 people. Each observed a vehicle coming out of the harbor and the entrance to the harbor. | Surveyor required is 4 people. Each observing one segment intersection of four intersection. |
| 2      | Technical survey                      | Survey conducted by recording the type and number of vehicles that enter or exit   | The survey was conducted by recording the type and number of passing vehicles                |

|   |                          |   |   |
|---|--------------------------|---|---|
|   |                          | from the harbor.  | in each segment of the intersection of four.  |
| 3 | The timing of the survey | The survey was held on Sunday, June 16, 2013 at 06:00 to 8:00 pm and at 15:00 to 17:00 pm.                  | Surveys were conducted on Monday, June 17th, 2013 at 7:00 to 9:00 pm.   |
| 4 | Working Equipment used   | Surveyform, used to record the data of the survey include the type of vehicle, time and number of vehicles. | Survey form, is used to record the data of the survey include the type of vehicle, time and number of vehicles. |

**Processing and Data Analysis**

From the collection of primary and secondary data then they were analyzed. All of this analysis is to determine some characteristics which must be fulfilled at this time and for a period of 5 (five) years later. The things to be analyzed is as follows.

- Number of Ships
- Number of vehicles in and out of the harbor
- Dock Infrastructure
- Parking Infrastructure
- Road Infrastructure in the Hinterland area

**III. Research Analysis Results And Discussion**


**Ship volume**

The volume of the ship which is the number of ships mooring every month for one year in 2012 either licensed or unlicensed presented in the following table.

**Table 2.** The volume of the port in 2012

| NUMBER | MONTH        | VOLUME (UNIT) | PERCENTAGE     |
|--------|--------------|---------------|----------------|
| 1      | January      |               | 8,03%          |
| 2      | February     | 163           | 6,40%          |
| 3      | March        | 180           | 7,08%          |
| 4      | April        | 189           | 7,44%          |
| 5      | May          | 191           | 7,51%          |
| 6      | June         | 194           | 7,63%          |
| 7      | July         | 203           | 7,99%          |
| 8      | August       | 206           | 8,11%          |
| 9      | September    | 228           | 8,95%          |
| 10     | October      | 243           | 9,54%          |
| 11     | November     | 253           | 9,94%          |
| 12     | Desember     | 289           | 11,37%         |
|        | <b>TOTAL</b> | <b>2542</b>   | <b>100,00%</b> |

Source: Results of Analysis




**Figure 2.** Graph the volume percentage of the vessel in 2012

Trends in the number of ships in the fishing port each year is different, because affected by fishing season. Based on the above chart, it can be seen that the volume of the vessel in 2012 was highest in December



that is 11.37% number of 289 ships of various sizes. The maximum of the next data to be sampled as the basis for calculating the adequacy of the pier. Here is a daily volume licensed ship in December 2012 based on the size of the vessel:



**Figure 3.** Graph the maximum number of mooring ships in 1 day

Based on the Minister of Marine and Fisheries Decree No. 165 In 2000, one of the criteria for Fishery Harbor Beach is the anchor mooring facilities for fishing boats with at least 10 GT.

From the data above, obtained maximum number of vessels in one day was 57 vessels, or 24.46% of the total number of ships for a month. For the size of the largest ships that dock is a 10 GT with the maximum number of ships mooring in one day was 9 ships or some 15.79%. While the vessel is less than 10 GT number 8 vessels or 14.04% and more than or equal to 10 GT number 49 ships or 85.96%.

**Adequacy of Dock**

Based on the Minister of Marine and Fisheries Decree No. 165 In 2000, the port has a quay length of coastal fisheries at least 100 meters and can accommodate at least 30 boats or 300 GT at one time.

Coastal fishing port Situbondo City has dock, that is landing dock / unloading and mooring docks which are differentiated according to the size of the ship. The effective length of each pier can be seen in the table below:

Long landing dock / unloading required for today can be seen from the following calculation:

The landing dock / loading for vessel size > 30 GT

loading and unloading time : 2 hours

port operational time : 24 hours

then the value  $\gamma$  : 12 hours

size vessels 10 GT, LOA : 17.6 m

number of vessels anchored : 100 ships

$$Ld = \frac{N}{\gamma} L + 0,15L$$

$$Ld = \frac{100}{12} 17,6 + 0,15(17,6): 168.67 \text{ m} \approx 168 \text{ m}$$

So the landing dock needed for today is 168m. It can be used for  $\pm 3$  vessels simultaneously with the space between the freedom of the ship is  $0.15 L = 2,64\text{m}$ . From the above calculation it can be seen that the length of the pier that available is sufficient for current needs. The length of the pier is used along 168m of quay length of 200 m that provided.

From the analysis of the adequacy of the dock, then by changing the way the mooring of vessels dilated / transverse require less space so the ship mooring space requirements can be fulfilled until 2016. Transportation management at the dock that is needed is revamping the layout, repair ships queuing system.

**Adequacy of parking space**

**Analysis of Existing Parking Space**

The total effective area available parking area is 3402.88 m<sup>2</sup>. The area of 1458.38 m<sup>2</sup> of which is a parking area for cars and other 1944.5 m<sup>2</sup> is truck parking area. While the parking area for pick-ups, motorcycles, and unmotorized vehicles are not available.

In determining the need for parking space with the approach used accumulated the highest amount of accumulated parking. Based parking accumulation that occurred during the investigation in the field, the need for a parking space can be calculated by determining the number of vehicles at the time of maximum parking accumulation. The following is a calculation of existing parking space requirements:

- Motor: 284 x 1.5 : 426 m<sup>2</sup>
- Car : 34 x 12.5 : 425 m<sup>2</sup>
- Truck: 12 x 42.5 : 510 m<sup>2</sup>
- Unmotor : 57 x 1,5 : 85.5 m<sup>2</sup>
- Pickup : 60 x 15: 900 m<sup>2</sup>

From the above calculations for a car parking space requirement is 425 m<sup>2</sup> (29.14%) and a parking space for a truck that is 510 m<sup>2</sup> (26.23%). It can be seen that the parking spaces are available to provide for parking today.

**Parking Space Needs Analysis 5 Year Upcoming**

Predicted increase in the number of vehicles in 2012 – 2016 based on the secondary data obtained from the fisheries harbor Manager cottage Mimboare as follows:

- Motor : 4.78% per year
- Car : 5.02% per year
- Truck : 12.50% per year
- Pick-up : 12.50% per year

Calculations predicted number of vehicles parked in the accumulation of 2012 - 2016 can be seen in the following table:

**Table 3.** Parking accumulation data in 2007-2012

| VEHICLE<br>(unit) | YEAR |      |      |      |      |      |
|-------------------|------|------|------|------|------|------|
|                   | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
| <b>MOTOR</b>      | 233  | 244  | 256  | 269  | 283  | 297  |
| <b>CAR</b>        | 27   | 29   | 30   | 32   | 33   | 35   |
| <b>TRUCK</b>      | 7    | 8    | 9    | 10   | 11   | 13   |
| <b>PICK-UP</b>    | 34   | 39   | 45   | 51   | 58   | 67   |

**Table 4.** Predicted parking accumulation in 2011-2016

| VEHICLE<br>(unit) | YEAR |      |      |      |      |      |
|-------------------|------|------|------|------|------|------|
|                   | 2011 | 2012 | 2013 | 2014 | 2015 | 2016 |
| <b>MOTOR</b>      | 283  | 297  | 312  | 327  | 343  | 359  |
| <b>CAR</b>        | 33   | 35   | 37   | 39   | 41   | 43   |
| <b>TRUCK</b>      | 11   | 13   | 15   | 17   | 19   | 21   |
| <b>PICK-UP</b>    | 58   | 67   | 76   | 86   | 96   | 108  |

Source: Results of Analysis

Based on the analysis of the parking accumulation predictions 2012 - 2016, the prediction of parking space requirements in 2016 can be calculated by the following calculation:

- Motor: 359 x 1,5 : 538.13 m<sup>2</sup>
- Car : 43 x 12.5 : 542.92 m<sup>2</sup>
- Truck: 22 x 42.5 : 919.04 m<sup>2</sup>
- Pick-up : 108 x 12.5 : 1351.52 m<sup>2</sup>

From the above calculation, predicted the need for car parking spaces increased to 538.13 m<sup>2</sup> and for the truck is 919.04 m<sup>2</sup>. The increase in parking space requirements increased by 94.93%. While parking space for pick-up which was not originally provided, in 2016 the number increased to 108 units. This condition requires to provide parking space for pick-up as it may not be left parked in any place considering its function as a transporter of fish.

**Alternative of Parking Adequacy**

**1. Motor cycle**

The majority of visitors who use the port of the motor is intended for tours. Because of parking spaces for motorcycles is not provided, the riders parked their bikes around the fish auction place to their liking. By the

increasing number of motorcycles in 2016 will further aggravate the situation if a parking space for motor still not provided.

Breakwater is a destination for visitors who aim to travel. Seeing this situation, the best solution is to provide motorcycle parking spaces in the area of the breakwater. The following is the calculation of the adequacy of motorcycle parking spaces if bike parking spaces in the breakwater area is planned :


number of motor : 359 engine  
 parking space unit of motor : 0.75 m x 2.00 m  
 breakwater width : 7.5 m  
 long breakwater (motorcycle parking area) : 172 m

If it is planned to use the parking pattern 2 sides, then the length of parking spaces required is:

$$\frac{359 \times 0,75 \text{ m}}{2} \leq 172 \text{ m} \times 2$$

$$269,25 \text{ m} \leq 344 \text{ m}$$

From the above calculation it can be seen that the parking spaces are provided to meet the needs of 688 m<sup>2</sup> park is 538.5 m<sup>2</sup>. Here is a plan drawing motorcycle parking spaces:



**Figure 4.** Parking a motor with a pattern of 2 sides

## 2. Car

Same with visitors using motors, majority of visitors who use the car also aims to tour and breakwater is their destination. So for a car parking space should also be provided in the area of the breakwater. The following is the calculation of the adequacy of car parking spaces if the planned car parking spaces in the breakwater area:


number of cars : 43 cars  
 parking space unit of car : 2.50 m x 5.00 m  
 breakwater width : 7.5 m  
 long breakwater (car park area) : 130 m

If it is planned to use the parking one side of the pattern, then the length of parking spaces required is:

$$43 \times 2,50 \text{ m} \leq 130 \text{ m}$$

$$108,58 \text{ m} \leq 130 \text{ m}$$

From the above calculation it can be seen that the car parking spaces are provided which can meet the needs of 650 m<sup>2</sup> parking is 542.9 m<sup>2</sup>. Here is a picture of car parking space plan:



**Figure 5.** The car park to the pattern of one side

### 3. Truck and Pick Up

The purpose of the port visitors who use truck and pick up is for transporting fish and distributed to a particular place. Fish taken from public fisherman, must be pass through the fish auction first. However, for certain companies that have their own fishing boats, truck or pick-up can simply take the fish from the boat.

To overcome the problem of truck parking demand and a pick up in 2016, a truck and pick up parking space can be merged because their function is same. The parking spaces should not be far from the place of extraction of fish.

The parking spaces are required for the truck is 919.04 m<sup>2</sup> and for the pick up is 1351.52 m<sup>2</sup>. So, the total requirement is 2270.56 m<sup>2</sup>. The parking spaces that can be used is the area of the parking space of Fish Auction Place area as wide of 1944.5 m<sup>2</sup> and current car parking space area of 1458.38 m<sup>2</sup>. So, the total area of the parking area is 3402.88 m<sup>2</sup>.

From the analysis above, available parking spaces area 3402.88 m<sup>2</sup> can fulfill the parking needs of truck and pickup that is 2270.56 m<sup>2</sup>.

For a port visitor who use car and motorcycle aiming to shop, can be directly parked their vehicles in front of the parking area stalls selling that already available.

From the analysis of the adequacy of parking, then by using the tip of the breakwater area for motorcycle parking space (688 m<sup>2</sup>) with a pattern of two sides and the base of the breakwater area for car parking (650m<sup>2</sup>) with a pattern of one side and a parking area that has been available previously for the truck and pick-up, parking space requirements can be met. Transportation parking management required is revamping the layout of the parking of vehicles, repair queuing system, and policies related to the tariff.

### Adequacy Analysis on Regional Road Hinterland Road Geometric

The analyzes were performed at the intersection of four unsignal junction that closest to the port gate. This road has a width of ± 5 m for segment SumberAnyar Village direction, ± 10 m for the segment toward the port, ± 7 m for the segment towards the city and ± 10 m for the segment direction KarangTekok Village. This road is a two lane road and two-way.

### Traffic volume

Traffic volume obtained from the traffic results survey on the same day, which is Monday at 7:00 to 9:00 pm time is assumed to be stable enough to capture the data traffic flow, with a duration about 5 minutes. The survey was conducted in four segments, namely, the direction of the SumberAnyar Village, direction of the harbor, direction of the city, and the direction of the Village of KarangTekok. From the results of this survey obtained the magnitude of the flow of traffic on each segment. So it can be known volume of vehicles involved in each road segment. Here are the results of the vehicular traffic volume calculation :

**Table 5.** Volume LV (pcu / h)

| Origin              | Destination  |          |                     |                     |
|---------------------|--------------|----------|---------------------|---------------------|
|                     | Fishery Port | The City | SumberAnyar Village | KarangTekok Village |
| Fishery Port        | 0            | 19       | 5                   | 1                   |
| The City            | 10           | 0        | 19                  | 1                   |
| SumberAnyar Village | 6            | 16       | 0                   | 0                   |
| KarangTekok Village | 1            | 2        | 0                   | 0                   |

Source: Results of Analysis

**Table 6.** Volume HV (pcu / h)

| Origin              | Destination  |          |                     |                     |
|---------------------|--------------|----------|---------------------|---------------------|
|                     | Fishery Port | The City | SumberAnyar Village | KarangTekok Village |
| Fishery Port        | 0,0          | 24,8     | 1,5                 | 0,0                 |
| The City            | 17,3         | 0,0      | 10,5                | 2,3                 |
| SumberAnyar Village | 0,0          | 9,0      | 0,0                 | 0,8                 |
| KarangTekok Village | 0,8          | 1,5      | 0,0                 | 0,0                 |

Source: Results of Analysis

**Table 7.** Volume MC (pcu / h)

| Origin              | Destination  |          |                     |                     |
|---------------------|--------------|----------|---------------------|---------------------|
|                     | Fishery Port | The City | SumberAnyar Village | KarangTekok Village |
| Fishery Port        | 0,0          | 44,5     | 74,5                | 11,3                |
| The City            | 48,5         | 0,0      | 114,3               | 17,3                |
| SumberAnyar Village | 74,5         | 78,5     | 0,0                 | 3,5                 |
| KarangTekok Village | 9,3          | 8,0      | 5,8                 | 0,0                 |

Source: Results of Analysis

From the above data, it can be seen  $Q_{TOT}$  namely:

$$Q_{TOT} = Q_{LV} + Q_{HV} + Q_{MC}$$

$$Q_{TOT} = 80 + 68.5 + 490$$

$$Q_{TOT} = 638.5 \text{ pcu / hour}$$

### Capacity and Degree of Saturation

In determining capacity, necessary steps in accordance with MKJI calculations. Here are the steps in determining the capacity :

1) The value of the base capacity ( $C_0$ )

This intersection has four arms, each of which has 2 row and 2 lanes. Therefore, according to MKJI 97, this intersections are type 422, so it has  $C_0$  value 2900 pcu / hour.

2) Approach width adjustment factor ( $F_w$ )

$$F_w = 0.70 + 0.0866 (W_i)$$

$$F_w = 0.70 + 0.0866 (4)$$

$$F_w = 1.046$$

3) The adjustment factor is the main street median ( $F_M$ )

Because there are no medians on main roads, then the value of  $F_M$  is 1.00.

4) The adjustment size of the city factor ( $F_{CS}$ )

Situbondo is a very small town with a population <0.1 million, then the  $F_{CS}$  value was 0.82.

5) The adjustment type of side barrier road environment and non-motorized vehicles factor

Type of RE road environment class = commercial

Side barriers SF class = low

The ratio of non-motorized vehicles  $P_{UM}$  = 1.0

So,  $F_{RSU}$  = 0.86

6) Turn left adjustment factor ( $F_{LT}$ )

$$F_{LT} = 0.84 + 1.61 (P_{LT})$$

$$F_{LT} = 0.84 + 1.61 (0.25) = 1.24$$

7) Turn Right adjustment factor ( $F_{RT}$ )

Due to the intersection with four arms, then the value of the  $F_{RT}$  is 1.0.

8) Minor road flow adjustment factor ( $F_{MI}$ )

$$F_{MI} = 1.19 \times PMI_2 - PMI + 1.19 \times 1.19$$

$$F_{MI} = 1.19 \times 0.52 \text{ to } 1.19 \times 0.5 + 1.19$$

$$F_{MI} = 0.297 \text{ to } 0.595 + 1.19$$

$$F_{MI} = 0.892$$

From the data above, the capacity can be calculated as follows:

$$C = C_0 \times F_w \times F_M \times F_{CS} \times F_{RSU} \times F_{LT} \times F_{RT} \times F_{MI}$$

$$C = 2900 \times 1.046 \times 1.00 \times 0.82 \times 0.86 \times 1.24 \times 1.0 \times 0.892$$

$$C = 2366.075 \text{ pcu / hour}$$

So the degree of saturation (DS) is:

$$DS = Q_{TOT} / C$$

$$DS = 635 / 2366.075$$

$$DS = 0.29$$

From the analysis above obtained value of DS was 0.29, which means that the intersection of four levels of service B, namely:

1. Flow is stable with moderate traffic volume and speed began to be restricted by traffic conditions.
2. The traffic density low and internal resistance not affect the speed of traffic.
3. The driver still has enough freedom to choose the speed and lane to use.

### Hinterland Regional Traffic Analysis 5 Year Upcoming

#### • Predicted increase in the number of vehicles in 2016


Based on data from the Central Statistics Agency Situbondo City, obtained number of vehicles in 2007 - 2010 are as follows:

**Table 8.** The volume of vehicles in Situbondo in 2007-2010 (units)


| Vehicles | 2007  | 2008  | 2009  | 2010  |
|----------|-------|-------|-------|-------|
| MC       | 43791 | 53149 | 61864 | 64253 |
| LV       | 4123  | 5004  | 5825  | 6050  |
| HV       | 3759  | 4562  | 5310  | 5515  |

Source: Results of Analysis


From the above data, to predict the increase in the number of vehicles in 2016 can use a Line Linear Equations.



**Figure 6.** Graph linear equations MC in 2007-2010



**Figure 7.** Graph linear equations LV in 2007-2010



**Figure 8.** Graph linear equations HV years 2007-2010

From the above linear equation, can be seen the number of vehicles in the year 2011 - 2016 are as follows:

**Table 9.** Prediction of volume of vehicles in Situbondo 2016 (units)

| Vehicles | 2011  | 2012  | 2013  | 2014  | 2015   | 2016   |
|----------|-------|-------|-------|-------|--------|--------|
| MC       | 73289 | 80299 | 87309 | 94319 | 101329 | 108339 |
| LV       | 6900  | 7560  | 8220  | 8880  | 9540   | 10200  |
| HV       | 6291  | 6892  | 7494  | 8096  | 8697   | 9299   |

Source: Results of Analysis

From the analysis above it can be seen that the increase in the number of vehicles in Situbondo from year to year, an average of 9.12%. So, the prediction of the number of vehicles per hour in the hinterland in 2016 are as follows:

**Table 10.** Volume LV 2016 (pcu / h)

| Origin              | Destination  |          |                     |                     |
|---------------------|--------------|----------|---------------------|---------------------|
|                     | Fishery Port | The City | SumberAnyar Village | KarangTekok Village |
| Fishery Port        | 0            | 29       | 7                   | 2                   |
| The City            | 15           | 0        | 29                  | 2                   |
| SumberAnyar Village | 9            | 24       | 0                   | 0                   |
| KarangTekok Village | 2            | 2        | 0                   | 0                   |

Source :Analisis Results

**Table 11.** Volume of HV 2016 (pcu / h)

| Origin              | Destination  |          |                     |                     |
|---------------------|--------------|----------|---------------------|---------------------|
|                     | Fishery Port | The City | SumberAnyar Village | KarangTekok Village |
| Fishery Port        | 0,0          | 38,3     | 2,3                 | 0,0                 |
| The City            | 26,7         | 0,0      | 16,2                | 3,5                 |
| SumberAnyar Village | 0,0          | 13,9     | 0,0                 | 1,2                 |
| KarangTekok Village | 1,2          | 2,3      | 0,0                 | 0,0                 |

Source: Results of Analysis

**Table 12.** Volume MC 2016 (pcu / h)

| Origin              | Destination  |          |                     |                     |
|---------------------|--------------|----------|---------------------|---------------------|
|                     | Fishery Port | The City | SumberAnyar Village | KarangTekok Village |
| Fishery Port        | 0,0          | 68,8     | 115,3               | 17,4                |
| The City            | 75,0         | 0,0      | 176,8               | 26,7                |
| SumberAnyar Village | 115,3        | 121,4    | 0,0                 | 5,4                 |
| KarangTekok Village | 14,3         | 12,4     | 8,9                 | 0,0                 |

Source: Results of Analysis

From the above data, it can be seen  $Q_{TOT}$  for 2016. They are:

$$Q_{TOT} = Q_{LV} + Q_{HV} + Q_{MC}$$

$$Q_{TOT} = 119 + 106 + 758$$

$$Q_{TOT} = 982 \text{ pcu / hr}$$

### Degree of Saturation (DS)

The degree of saturation (DS) in 2016 are as follows:

$$DS = Q_{TOT} / C$$

$$DS = 982 / 2366.075$$

$$DS = 0.42$$

From the analysis above DS value obtained was 0.42, which means that the intersection of four had a level of service C, namely :

1. Flow is stable but the speed and movement of vehicles controlled by the higher traffic volume.
2. The traffic density was moderate due to the traffic internal resistance increased.
3. The driver has a limitation to select speed, change lanes or precede.

### Alternative Traffic Hinterland

From the analysis of the above study concluded that traffic conditions hinterland today to five years is still feasible. Associated with urban traffic regulations that HV vehicles may not cross the city need an alternative to the HV traffic flow towards Situbondo.

There is a road leading Situbondo port right next to the gate that was originally supplied to the HV vehicles will be out from Situbondo towards Banyuwangi. However, it doesn't work because the width road is

less than the standard that is 5 m. In order to its function, the way need to be widened. This method is possible because in the right and left of the road there are road shoulder width respectively  $\pm 1.5 - 2$  m.

#### **IV. Conclusions And Recommendations**

##### **Conclusion**

Based on the results of research and analysis of data, it can be concluded as follows:

1. Dock Adequacy
  - a) Needs of existing docks unloading and mooring for boats less size and more than 10T still be fulfilled properly.
  - b) Unloading dock for ship size is less or more than 10 GT still be met but overload jetty mooring for vessels up to 254% the size of more than 10 GT and 128% for vessels less than 10 GT size.
  - c) By changing the way the mooring of vessels dilated / transverse require less space so the ship mooring space requirements can be fulfilled until 2016.
2. Parking Space Adequacy
  - a) Existing parking spaces are only available for cars and trucks only and enough for parking needs.
  - b) The number of vehicles entering the port increased, so that parking spaces be overloaded, so it is needs to provide parking spaces for motorcycles and pick-up.
  - c) By utilizing tip of the breakwater area for motorcycle parking space ( $688 \text{ m}^2$ ) with a pattern of two sides and the base of the breakwater area for car parking ( $650 \text{ m}^2$ ) with a pattern of one side and a parking area that has been available previously for the truck and pick-up, parking space requirements can be met.
3. Adequacy Road at Hinterland Region
  - a) Review existing traffic volume area (intersection of four non signal) can meet and have a level of service B but for HV vehicles heading towards Situbondo must pass through the city because the roads are too narrow and can not meet the needs.
  - b) With the increasing number of vehicles in 2016, the level of service drops to C but still decent.
  - c) By widening the ring road towards Situbondo according to standard (7 m), it can be an alternative to the HV vehicle towards Situbondo.

##### **Recommendations**

In accordance with the secondary data, field observations, and processed data, then we give some suggestions which is also an alternative solution of the above problems:

1. Alternatives to address the needs of ship mooring space in 2016 is to change the way aft mooring of vessels become dilated.
2. To meet the needs of car parking spaces in the port 2016 can capitalize on the breakwater area for motorcycles and cars as well as parking spaces that have been there before can be used for truck and pick-up.
3. In accordance with the rules of urban traffic that HV vehicles are prohibited from passing on city streets, then to widen the ring road towards Situbondo who has been there can be a solution.

##### **References**

- [1]. Morlok, Edward K. Pengantar Teknik dan Perencanaan Transportasi. Erlangga. Jakarta. 1988.
- [2]. Nasution, H.M.N.MS.Tr. Manajemen Transportasi Ghalia Indonesia. Jakarta. Juni 1996.
- [3]. Ofyar Z. Tamin, 2000, Perencanaan dan Permodelan Transportasi, Penerbit ITB, Bandung.
- [4]. Triatmodjo, Bambang. Pelabuhan. Beta Offset. Yogyakarta. Februari 1996.
- [5]. Widyahartono, Bob. Manajemen Transportasi. Depdikbud Universitas Terbuka. Jakarta. 1986.
- [6]. -----, 1996 Pedoman Teknis Penyelenggaraan Fasilitas Parkir. Jakarta: Direktorat Jenderal Perhubungan Darat, Departemen Perhubungan.