LEMBAR

HASIL PENILAIAN SEJAWAT SEBIDANG ATAU PEER REVIEW KARYA ILMIAH: JURNAL ILMIAH

Judul Karya Ilmiah (Paper)	: Enhancing bamboo reinforcement using a hose	e-clamp to increase bond-stress and slip resistance
Jumlah Penulis	: 4 Orang (1. Muhtar, 2. Sri Murni Dewi, 3. Wisnumurt	i 4. As'ad Munawir)
Status Pengusul	: Penulis pertama / penulis ke / penulis koresponden	si**
Identitians Jurnal/Prosiding	: a. Nama Jurnal/ Prosiding	: Journal of Building Engineering
	b. ISSN/ISBN	: 2352-7102
	c. Tahun Terbit, (tempat pelaksanaan jika prosiding)	: 2019
	d. Penerbit/Organiser	: Elsevier B.V
	e. Alamat repository PT/ Web	: http://repository.unmuhjember.ac.id/4024/
	f. Terindek di (jika ada)	: SCOPUS (Q1 SJR 0.97)
Kategori Publikasi Artikel Ilmiah	: 🗸 Jurnal Internasonal Bereputasi	
(Beri √ pada kategori yang tepat)	Jurnal Internasional	
	Jurnal Nasional Terakreditasi	
	Jurnal Nasioanl Tidak Terakreditasi	
	Jurnal Nasional Terindeks DOAJ dll	
	Prosidng Forum Ilmiah Internasional	
	Prosiding Forum Ilmiah Nasioanl	

Hasil Penialain Peer Review :

	N	ilai Maksimal Ju	rnal Ilmiah (Isil	can di kolom yang	sesuai)	
Komponen Yang Dinilai	Internasonal Bereputasi	Internasional	Nasional Terakreditasi	Nasioanl Tidak Terakreditasi	Nasional Terindeks DOAJ dll	Nilai Akhir yang diperoleh
Kelengkapan dan kesesuain unsur isi jurnal (10%)	4					4
Ruang Lingkup dan kedalaman pembahasan (30%)	12					12
Kecukupan dan kemutakhiran data/informasi dan metodelogi (30%)	12					12
Kelengkapan unsur dan kualitas penerbit (30%)	12					12
Total 100%	40					40
Kontribusi Pengusul (Penulis Pertama/ Anggota Utama)						60%×40 = 24
Komentar Peer Review	 Tentang Kelo Tentang Rua Kecukupan, I Kelengkapan Indikasi Plag Kesesuian bi 	ngkapan dan kese ng Lingkup dan ke Kemutakhiran dat unsur kualitas pe iasi:	isuain unsur : edalaman pembah a serta metodelogi nerbit : .t	ugal Congliap Lingliap asan: trainsche Defournessi utos prenere Stal Emmi Guzvoi C	Simai unsur Liset filmai ten palas alla M candisa can angot news larity 15 ndang 14	Impad Sebuch jurn trang beton bertula sultig lunks in 1/2 fer sort men bolom show the tolstruter.). Jur 20 20 20 20 20 20 20 20

Malang, April 2020 Reviewer 1 the

(**Prof. Dr. Ir. Sri Murni Dewi, MS.**) NPK/NIP. 195112111981032001 Unit kerja: Teknik Sipil UB Malang Jafung : Guru Besar Bidang Ilmu : Teknik Sipil

LEMBAR

HASIL PENILAIAN SEJAWAT SEBIDANG ATAU PEER REVIEW KARYA ILMIAH: JURNAL ILMIAH

Judul Karya Ilmiah (Paper) : Enhancing bamboo reinforcement using a hose-clamp to increase bond-stress and slip resistance Jumlah Penulis : 4 Orang (1. Muhtar, 2. Sri Murni Dewi, 3. Wisnumurti 4. As'ad Munawir) Status Pengusul : Penulis pertama / penulis ke.... / penulis korespondensi** Identitians Jurnal/Prosiding : a. Nama Jurnal/ Prosiding : Journal of Building Engineering b. ISSN/ISBN : 2352-7102 c. Tahun Terbit, (tempat pelaksanaan jika prosiding) : 2019 d. Penerbit/Organiser : Elsevier B.V e. Alamat repository PT/ Web : http://repository.unmuhjember.ac.id/4024/ f. Terindek di (jika ada) : SCOPUS (Q1 SJR 0.97) : $\sqrt{1}$ Jurnal Internasonal Bereputasi Kategori Publikasi Artikel Ilmiah Jurnal Internasional (Beri √ pada kategori yang tepat) Jurnal Nasional Terakreditasi Jurnal Nasioanl Tidak Terakreditasi Jurnal Nasional Terindeks DOAJ dll Prosidng Forum Ilmiah Internasional Prosiding Forum Ilmiah Nasioanl

Hasil Penialain Peer Review :

	N	ilai Maksimal Ju	sesuai)				
Komponen Yang Dinilai	Internasonal Bereputasi	Internasional	Nasional Terakreditasi	Nasioanl Tidak Terakreditasi	Nasional Terindeks DOAJ dll	Nilai Akhir yang diperoleh	
Kelengkapan dan kesesuain unsur isi jurnal (10%)	4					3	
Ruang Lingkup dan kedalaman pembahasan (30%)	12					12	
Kecukupan dan kemutakhiran data/informasi dan metodelogi (30%)	12					12	
Kelengkapan unsur dan kualitas penerbit (30%)	12					12	
Total 100%	40					39	
Kontribusi Pengusul (Penulis Pertama/ Anggota Utama)				0		60 20 × 39 = 23,9	
Komentar Peer Review	 Tentang Kele Tentang Rua Kecukupan, Kelengkapan Indikasi Plag Kesesuian bi 	engkapan dan kese ng Lingkup dan k Kemutakhiran dat unsur kualitas pe giasi : A.J.A.K dang ilmu :	esuain unsur Ne edalaman pembal a serta metodelog enerbit : N4. N 4 forbe ad. 4	ung at lengt Ruang (pasan: Forsep 7 kinuba i: Referenti: s logo 7 logo 7	ap Limai Uns mglup Ritioi als, Peintotha link bond fress ang at relevo inc of virg stan, purna vier) inty 15 % f. brdang 1	ur IMPAD Party jur Bidang tentang bold san poudalady, No Vs Sip, Articel dit Dan Austriken, berkualitos Q, dg P Aman lum penulis	nal BRC Velty is tou metode enertit

April 2020 Malang, ... Reviewer To

(**Prof. Dr. Ir. Rudy Socnoko, M.Eng.Sc.**) NPK/NIP. 194909111984031001 Unit kerja : Teknik Mesin UB Malang Jafung : Guru Besar Bidang Ilmu : Teknik Mesin * 0

D

>

1.0

0 0 1 0



🕱 Inggris 🔹 🗲 Indonesia 👻 Terjemahkan pesan

This message was sent automatically.

Ref: JOBE_2019_257

kepada saya 🔻

Title: Strengthening of bamboo reinforcement using a hose clamp in efforts to increase bond stress and slip resistance Journal: Journal of Building Engineering

Dear Dr. Muhtar,

Thank you for submitting your manuscript for consideration for publication in Journal of Building Engineering. Your submission was received in good order.

To track the status of your manuscript, please log into EVISE# at: http://www.evise.com/evise/faces/pages/navigation/NavController.jspx?JRNL_ACR=JOBE and locate your submission under the header 'My Submissions with Journal' on your 'My Author Tasks' view.

Thank you for submitting your work to this journal.

Kind regards,

Journal of Building Engineering

Have questions or need assistance?

For further assistance, please visit our Customer Support site. Here you can search for solutions on a range of topics, find answers to frequently asked questions, and learn more about EVISEs via interactive tutorials. You can also talk 24/5 to our customer support team by phone and 24/7 by live chat and email.

Copyright © 2018 Elsevier B.V. | Privacy Policy

Elsevier B.V., Radarweg 29, 1043 NX Amsterdam, The Netherlands, Reg. No. 33156677.

[Pesan dipotong] Lihat seluruh email

🔨 Balas 🕪 Teruskan >

+

265 dari 374

Sen, 18 Feb 2019 21.52

÷

23

Nonaktifkan untuk: Inggris 🗙

e 2

=	M G	mail	Q Telusi	uri email						•	0	***	٢	Conversion Muhammadiyak Jember	
4	÷	0 0 T	© 0	D	•						259 dari 374	<	>	φ	31
		Reviews co	mplete an	d decisio	on pend	ding for you	ur manuscr	ipt JOBE_201	19_257 >	Kotak Ma	asuk X		•	Ø	
*	*	Journal of Buildir kepada saya 🔻	g Engineering	<evisesupport(< th=""><th>i)elsevier.com</th><th>m></th><th></th><th></th><td></td><td>Kam, 1</td><th>8 Apr 2019 04</th><td>27 Z</td><td>5 4</td><td>ł</td><td>0</td></evisesupport(<>	i)elsevier.com	m>				Kam, 1	8 Apr 2019 04	27 Z	5 4	ł	0
>		衣 Inggris •	> Indonesia	 Terjemahl 	(an pesan						Nonakti	ikan unt	uk: Inggri	is ×	
► ► ►		Reference: JOBE_2 Title: Strengthening Journal: Journal of I Dear Dr. Muhtar, I am pleased to info In the event that I n To track the status o I will inform you once	019_257 of bamboo reinto Building Engineer rm you that I hav eed to seek the o of your manuscrip re I have made a	preement using ring re received all pinion of an av ot, please log in decision.) a hose clar the required dditional revi nto EVISE®	mp in efforts to inc reviews, which I v lewer, you may se http://www.evise.c	vill now evaluate b will now evaluate b the status of you com/evise/faces/pa	and slip resistance efore making a decisio r manuscript revert briv ges/navigation/NavCor	en on your manus efty from 'Ready I ntroller.jspx?JRN	cript refer for Decisi	renced above. on' to 'Under I IOBE and go t	leview'. o 'My St	ubmission	ns".	+
		Thank you again for	submitting your	manuscript to	Journal of B	uilding Engineerin	ng and for giving m	e the opportunity to co	nsider your work.	0					>
		Kind regards,													
		Journal of Building	Engineering												

Have questions or need assistance?

For further assistance, please visit our Customer Support site. Here you can search for solutions on a range of topics, find answers to frequently asked questions, and learn more about EVISEs via interactive tutorials. You can also talk 24/5 to our customer support team by phone and 24/7 by live chat and email.

Copyright © 2018 Elsevier B.V. | Privacy Policy

Elsevier B.V., Radarweg 29, 1043 NX Amsterdam, The Netherlands, Reg. No. 33156677.

👟 Balas 🛛 ា Teruskan

10	Smail	Q Telu	suri email												6	•		0	Ĩ	10 ¥ 100	٢	Conversition Michaermadiyak Jeanher		
÷	0 T		0 0		:												246	dari 374	4	<	>	φ	1	2
	Revision rec	quested f	or JOBE	_201	9_257	7 ⋗ в	Kotak Ma	lasuk ×	¢												0	1		9
•	James LaFave (Jo kepada saya 💌	ournal of Build	ling Enginee	ering) <e< td=""><td>viseSupp</td><td>oort@else</td><td>evier.com></td><td>11></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Rab,</td><td>29 Mei</td><td>2019 08</td><td>1.21</td><td>*</td><td>*</td><td>ł</td><td>0</td><td>2</td></e<>	viseSupp	oort@else	evier.com>	11>								Rab,	29 Mei	2019 08	1.21	*	*	ł	0	2
	🛪 Inggris -	> Indonesia	🔹 Terjem	ahkan pe	san													Nonakt	ifkar	1 untuk	: Inggri	is ×		
	Ref: JOBE_2019_2 Title: Strengthening Journal: Journal of B	257) of bamboo reir Building Engine	forcement us ering	ing a hos	se clamp) in efforts	s to increa	rease bor	ond str	stress ar	ind slip i	resistan	nce										Н	5
	Dear Dr. Muhtar,																							
	Thank you for subm recommend reconsi	nitting your man ideration of you	uscript to the r paper follow	Journal o	of Buildin r revisior	ng Engine n. I therefe	eering. I h fore invite	l have co ite you to	comple to resu	leted the submit y	ie reviev vour ma	w of you anuscrip	ur manu pt after a	script, a addressi	nd a sun ng all rev	nmary i viewer (is appe comme	ended be ents.	elow.	The re	viewe	гБ		

When resubmitting your manuscript, please carefully consider all issues mentioned in the reviewers' comments, outline every change made point by point, and provide suitable rebuttals for any comments not addressed.

To submit your revised manuscript:

- Log into EVISE® at: http://www.evise.com/evise/faces/pages/navigation/NavController.jspx?JRNL_ACR=JOBE
- . Locate your manuscript under the header 'My Submissions that need Revisions' on your 'My Author Tasks' view

- · Click on 'Agree to Revise'
- · Make the required edits
- Click on 'Complete Submission' to approve

What happens next?

After you approve your submission preview you will receive a notification that the submission is complete. To track the status of your paper throughout the editorial process, log in to Evisee at: http://www.evise.com/evise/faces/pages/navigation/NavController.jspx?JRNL_ACR=JOBE.

Enrich your article to present your research with maximum impact. This journal supports the following Content Innovations:

Data in Brief (optional)

We invite you to convert your supplementary data (or a part of it) into a Data in Brief article. Data in Brief articles are descriptions of the data and associated metadata which are normally buried in supplementary material. They are actively reviewed, curated, formatted, indexed, given a DOI and freely available to all upon publication. Data in Brief should be uploaded with your revised manuscript directly to Journal of Building Engineering. If your Journal of Building Engineering research article is accepted, your Data in Brief article will automatically be transferred over to our new, fully Open Access journal, Data in Brief, where it will be editorially reviewed and published as a separate data article upon acceptance. The Open Access fee for Data in Brief is \$500.

Please just fill in the template found here:

http://www.elsevier.com/inca/publications/misc/dib_data%20article%20template_for%20other%20journals.docx. Then, place all Data in Brief files (whichever supplementary files you would like to include as well as your completed Data in Brief template) into a .zip file and upload this as a Data in Brief item alongside your Journal of Building Engineering revised. manuscript. Note that only this Data in Brief item will be transferred over to Data in Brief, so ensure all of your relevant Data in Brief documents are zipped into a single file. Also, make sure you change references to supplementary material in your Journal of Building Engineering manuscript to reference the Data in Brief article where appropriate.

Questions? Please send your inquiries to dib@elsevier.com. Example Data in Brief can be found here: http://www.sciencedirect.com/science/journal/23523409

I look forward to receiving your revised manuscript as soon as possible.

Kind regards

Dr. James M. LaFave, PE Receiving Editor (University of Illinois) Journal of Building Engineering

Comments from the editors and reviewers:

-Reviewer 1

The living environment of the world have deteriorated because of the massive use of fossil fuels, then the environmental problems have become the global problems in the latter half of the 20th century. In the attention in response to global warming issues and sustainable society, the manufacturing using natural materials has become actively. Bamboo, low cost, tast growing, and broad distribution of growth is expected to contribute significantly to earthquake-resistant construction and seismic retrofit technology in developing countries.

In this study, the authors studied for understanding the use of bamboo as reinforcement in concrete. There are various problems to establish bamboo reinforce concrete structure, but the most important problem is the poor bond between bamboo reinforcement and concrete. It is a very important attempt to quantitatively evaluate the structural characteristics based on several experiments and analysis. While I think there are some major issues to consider in this study, however, clarification of the details which did not found in this study is expected in future studies. It is judged that this paper is appropriate for the journal.

-Reviewer 2

Use of bamboo as reinforcement in concrete could be an attractive alternative of steel reinforcement, particularly in low-cost construction. Despite having moderate tensile strength, bamboo reinforced concrete has to face some practical challenges. Therefore, more research on the behaviour of bamboo reinforced concrete is required. In this regard, the effort of the authors of this research is appreciable.

However, I found that there are some major gaps in this research which need to be addressed. In this research, the authors did not mention the number of nodes in each bamboo reinforcement. Another important aspect of using bamboo inside the concrete is to overcome the challenge of biodegradation of bamboo in the presence of moisture with time. Authors

did use Sikadur® 752 to prevent the absorption of water but did not examine the effectiveness of that resin as a barrier to moisture. Additionally, Sikadur® 752 may play a significant role in increasing the tensile strength of bamboo reinforcement. However, in the paper, it was not mentioned whether the tensile strength of the bamboo was with or without Sikadur® 752 in figure 10. In the preparation of bamboo reinforcement, sand was also used to make the surface of the bamboo rough, but the specification of the sand was missing. Similarly, authors used the hose clamp to resist the slip between bamboo and concrete, however, the specification of the hose clamp material was not mentioned. In the preparation of bamboo reinforced concrete beams using hose clamp with different spacing, how the authors dealt with the interference of bamboo nodes and hose clamp was not. mentioned in the paper.

In case of a stat of pull out strength of concrete, how did specimen with hose-clamps without Sikadur – 752 show bond-stip failure and not showing any significant difference from the specimen with only bamboo? It seems the bamboo might slip through the hose-clamp during the test. Please explain this. The results of the test of pull out strength of concrete (figure 12) do not support the flexural test results (Figure 14, 15 and Table 2). Please explain this. Load-deflection relationship of BRC beams (Figure 16) is not clear. Please check the legation in this figure does not reflect the load-deflection behaviour of those beams. In case of measuring the slip in 4.4, one strain gauge is not sufficient to capture the elongation of bamboo reinforcement after the first crack occurs. Also, equation 5 apparent to be valid only for the elastic region. Equation 6 is not clear to me. ASTM E 2126 (line 732-734, 4.5) seems irrelevant to this work. Please explain. Equation 7 is not representative of the slip and bond stress relationship of the specimens. Please check this.

The finite element method used in this paper is not explained enough.

-Reviewer 3

- The topic of the paper is very up to date. However, the scale of the experimental model is too small which does not permit to make reliable analysis. The paper is written with not much care. In general it needs a very profound revision.

-Reviewer 4

The idea of the paper is interesting . Using domestic material such as bamboo bars as reinforcement especially in tropical area is a good idea, however, some points have to be verified:

The used loading scheme for the beams is four-point loading not three points loading. Correct.

* The chosen reference beam has to be reinforced by equivalent reinforcement to the bamboo bars. The area of two bars of 8 mm diameters is different from the areas for the used bamboo bars, especially the tensile strength is dissimilar. The tensile forces are not equals because the product of the area by the tensile strength for each material is unequal.

- · What is the loading rate for the pull out test?
- The entire paper has to be check for some grammatical errors and typos

MethodsX (optional)

We invite you to submit a method article alongside your research article. This is an opportunity to get full credit for the time and money you have spent on developing research methods, and to increase the visibility and impact of your work.

If your research article is accepted, your method article will be automatically transferred over to the open access journal, MethodsX, where it will be editorially reviewed and published as a separate method article upon acceptance. Both articles will be linked on ScienceDirect.

Please use the MethodsX template available here when preparing your article: https://www.elsevier.com/MethodsX-template. Open access fees apply.

Have questions or need assistance?

For further assistance, please visit our Customer Support site. Here you can search for solutions on a range of topics, find answers to frequently asked questions, and learn more about EVISEs via interactive tutorials. You can also talk 24/5 to our customer support team by phone and 24/7 by live chat and email.

Copyright © 2018 Elsevier B.V. | Privacy Policy

Elsevier B.V., Radarweg 29, 1043 NX Amsterdam, The Netherlands, Reg. No. 33156677.

Balas Teruskan

* 0

(3mail	Q Telusuri email	*	⊘ Ⅲ		Coversitan Mahasemadiyak Jokher	0
	0 0 i	ê C b b :		233 dari 374 🔍	>	\$	191
	Revision re-	quested for JOBE_2019_257_R1 🥦 Kotak Masuk 🛪				e 2	
-	James LaFave (J kepada saya 👻	Journal of Building Engineering) <evisesupport@elsevier.com></evisesupport@elsevier.com>	Ser	, 22 Jul 2019 18.56	☆ ·	6 I	0
	🛪 Inggris 🕶	> Indonesia ★ Terjemahkan pesan		Nonaktifkan ur	ntuk: Inç	jgris ×	
	Ref: JOBE_2019_2! Title: Strengthening Journal: Journal of	:57_RL g bamboo reinforcement using a hose-clamp to increase bond-stress and slip resistance f Building Engineering					+
	Dear Dr. Muhtar.						

Thank you for submitting your manuscript to the Journal of Building Engineering. I have received comments from reviewers on your manuscript. Your paper should become acceptable for publication pending suitable minor revision and modification of the article in light of the appended editorial comments.

When resubmitting your manuscript, please carefully consider all issues mentioned in the editor's comments, outline every change made point by point, and provide suitable rebuttals for any comments not addressed.

To submit your revised manuscript:

- Log into EVISE@ at: http://www.evise.com/evise/faces/pages/navigation/NavController.jspx?JRNL_ACR=JOBE
- . Locate your manuscript under the header 'My Submissions that need Revisions' on your 'My Author Tasks' view

>

- Click on 'Agree to Revise'
- Make the required edits
- · Click on 'Complete Submission' to approve

What happens next?

After you approve your submission preview you will receive a notification that the submission is complete. To track the status of your paper throughout the editorial process, log in to EVISE@ at: http://www.evise.com/evise/faces/pages/navigation/NavController.jspx?JRNL_ACR=JOBE.

Enrich your article to present your research with maximum impact. This journal supports the following Content Innovations:

Data in Brief (optional)

We invite you to convert your supplementary data (or a part of it) into a Data in Brief article. Data in Brief articles are descriptions of the data and associated metadata which are normally buried in supplementary material. They are actively reviewed, curated, formatted, indexed, given a DOI and freely available to all upon publication. Data in Brief should be uploaded with your revised manuscript directly to Journal of Building Engineering. If your Journal of Building Engineering research article is accepted, your Data in Brief article will automatically be transferred over to our new, fully Open Access journal, Data in Brief, where it will be editorially reviewed and published as a separate data article upon acceptance. The Open Access fee for Data in Brief is \$500.

Please just fill in the template found here:

http://www.elsevier.com/inca/publications/misc/dib_data%20article%20template_for%20other%20journals.docx. Then, place all Data in Brief files (whichever supplementary files you would like to include as well as your completed Data in Brief template) into a .zip file and upload this as a Data in Brief item alongside your Journal of Building Engineering revised manuscript. Note that only this Data in Brief item will be transferred over to Data in Brief, so ensure all of your relevant Data in Brief documents are zipped into a single file. Also, make sure you change references to supplementary material in your Journal of Building Engineering manuscript to reference the Data in Brief article where appropriate.

Questions? Please send your inquiries to dib@elsevier.com. Example Data in Brief can be found here: http://www.sciencedirect.com/science/iournal/23523409

I look forward to receiving your revised manuscript as soon as possible.

Kind regards,

Dr. James M. LaFave, PE Receiving Editor (University of Illinois) Journal of Building Engineering

Comments from the editors and reviewers: The authors are requested to please consider making the following suggested adjustments to the Title & Abstract of their manuscript (as well as to any other similar text in the main body of the paper):

- 1. "Strengthening bamboo reinforcement" --> "Enhancing bamboo reinforcement"
- 2. "construction because" --> "construction, because"
- 3. "caused by the failure of" --> "caused by failure of"
- 4. "using adhesive coating and roughness modification to the bamboo reinforcement" --> "using adhesive coatings or roughness modifications to bamboo reinforcement"
- 5. "resistance using" --> "resistance by using"

6. "model of load deflection and bond-stress and slip between the bamboo reinforcement and the concrete" --> "model of load vs. deflection and bond-stress vs. slip between bamboo reinforcement and concrete*

7. "The experiment uses a 75 mm" --> "The experiments use 75 mm"

8. "concrete beam." --> "concrete beams."

9. "specimens consist of 24 pieces of bamboo reinforced beam, one piece with \$ 8 mm steel reinforcement" -> "specimens comprise 24 bamboo-reinforced beams, one beam with 8 mm diameter steel reinforcement"

10. "The hose-clamp distance varies by 0 cm, 15 cm, 20 cm, and 25 cm." -> "Hose-clamp spacing varies by 0 cm, 15 cm, 20 cm, and 25 cm." (More importantly, though, is this even correct? Fig. 5 seems to show 10 cm, 15 cm & 20 cm, but I don't see any case w/ 0 cm or 25 cm. For 0 cm, is this actually supposed to mean that there is no hose-clamp, rather than that there are continuous hose-clamps? This is all very confusing & must be clarified!)

- 11. "The beam test uses the four-point" --> "Beam testing uses a four-point"
- 12. "The test result shows an" --> "Test results show an"
- 13. "and concrete." --> "and concrete, when hose-clamps are used."
- 14. "of load-deflection and bond-stress and slip between" --> "of load vs. deflection and bond-stress vs. slip between"

-Reviewer 4

-

MethodsX (optional)

We invite you to submit a method article alongside your research article. This is an opportunity to get full credit for the time and money you have spent on developing research methods, and to increase the visibility and impact of your work.

If your research article is accepted, your method article will be automatically transferred over to the open access journal, MethodsX, where it will be editorially reviewed and published as a separate method article upon acceptance. Both articles will be linked on ScienceDirect.

Please use the MethodsX template available here when preparing your article: https://www.elsevier.com/MethodsX-template. Open access fees apply.

Have questions or need assistance?

For further assistance, please visit our <u>Customer Support</u> site. Here you can search for solutions on a range of topics, find answers to frequently asked questions, and learn more about EVISE® via interactive tutorials. You can also talk 24/5 to our customer support team by phone and 24/7 by live chat and email.

Copyright @ 2018 Elsevier B.V. | Privacy Policy

Elsevier B.V., Radarweg 29, 1043 NX Amsterdam, The Netherlands, Reg. No. 33156677.

🐟 Balas 🛛 📫 Teruskan

= M Gmail	Q Telusuri email	⊘ ⊯	Covervian Matanenadyab Janhar
Tulis		233 dari 373 \prec	> ¢
C Kotak Masuk	Received revision JOBE_2019_257_R2 > Kotak Masuk ×		e 2
BerbintangDitunda	Journal of Building Engineering <evisesupport@elsevier.com> kepada saya *</evisesupport@elsevier.com>	Sel, 23 Jul 2019 12.29 🛣	° ♣ E
Penting	🛱 Inggris - > Indonesia - Terjemahkan pesan	Nonaktifkan untu	k: Inggris 🗙
 Terkirim Draf Kategori 	This message was sent automatically. Ref: JOBE_2019_257_R2 Title: Enhancing bamboo reinforcement using a hose-clamp to increase bond-stress and slip resistance.		
✓ Selengkapnya	Journal: Journal of Building Engineering Dear Dr. Muhtar,		
	Thank you for submitting your revised manuscript for consideration for publication in Journal of Building Engine order.	eering. Your revision was rec	eived in good
	To track the status of your manuscript, please log into EVISE® http://www.evise.com/evise/faces/pages/naviga and locate the submission under the header 'My Submissions with Journal' on your 'My Author Tasks' view.	(tion/NavController.jspx?JRNL	_ACR=JOBE
	We appreciate your submitting your revision to this journal.		
± ⊕ %	Journal of Building Engineering		
	Have questions or need assistance? For further assistance, please visit our <u>Customer Support</u> site. Here you can search for solutions on a range o questions, and learn more about EVISE® via interactive tutorials. You can also talk 24/5 to our customer suppor and email.	f lopics, find answers to frequ ort team by phone and 24/7 b	iently asked y live chat
	Convricted @ 2018 Elsovier B V Drivery Policy		
	Elsevier B.V., Radarweg 29, 1043 NX Amsterdam, The Netherlands, Reg. No. 33156877.		

[Pesan dipotong] Lihat seluruh email

*	Balas	ា Teruska

≡	M Gmail	Q	Telusuri email	-	0	***	Coversian National Justice	iyalı
	Tulis	÷			232 dari 373	<	¢ <	81
	Kotak Masuk		Your manuscript JOBE_2019_257_R2 has been accepted	> Kolak Masi	k ×		e 2	3
*	Berbintang Ditunda		James LaFave (Journal of Building Engineering) <evisesupport@elsevier.com> kepada saya 💌</evisesupport@elsevier.com>	Rab,	24 Jul 2019 20.27	'☆	•	0
>	Penting		🛱 Inggris 🔹 > Indonesia 👻 Terjemahkan pesan		Nonaktifk	an untuk	: Inggris ×	
>	Terkirim		Ref: JOBE 2019 257 R2					+
	Draf Kategori		Title: Enhancing bamboo reinforcement using a hose-clamp to increase bond-stress and silp resil Journal: Journal of Building Engineering	stance				
Ŷ	Selengkapnya		Dear Dr. Muhtar, I am pleased to inform you that your paper has been accepted for publication. My own comments the end of this letter.	s as well as any re	eviewer comment	s are ap	pended to	
			Your accepted manuscript will now be transferred to our production department. We will create a more about this here. Meanwhile, you will be asked to complete a number of online forms require from you during the production process, then we will contact you about that.	proof, which you ed for publication.	will be asked to c If we need addit	heck. Y onal inte	'ou can read ormation	
	± ଦ ∿		Thank you for submitting your work to the Journal of Building Engineering. We hope you consider Kind regards,	r us again for futu	re submissions.			>
			Dr. James M. LaFave, PE Receiving Editor (University of Illinois) Journal of Building Engineering					

Comments from the editors and reviewers: Nice work.

Have questions or need assistance?

.....

3000

For further assistance, please visit our <u>Customer Suggert</u> site. Here you can search for solutions on a range of topics: find answers to frequently asked questions, and learn more about EVISEs via interactive tutorials. You can also talk 24/5 to our customer support team by phone and 24/7 by live chat and email.

Copyright © 2018 Elsevier B.V. | Privacy Policy

Elsevier B.V., Radarweg 29, 1043 NX Amsterdam, The Netherlands, Reg. No. 33156677.

[Pesan dipotong] Lihat seluruh email



		C			1								229	dari 374	<	>	ф
Track your	r article	[JOBE	1008	96] a	accept	ted in .	Journ	al of Bi	uilding	Engin	eering	😕 Kola	k Masuk 🕽	×		e	<u>9</u> (
Elsevier - Articl	la Statue de	ticle Status	Gelsevier	come					1000			P	ab 24 Jul	2010 22 0	15 A		
 kepada saya 🔻	ie Status 🗠	none_orange	(Leiseviei	A GIN P								I.	10, 24 001	201922.0	in 14	6 0.979	•
🗙 Inggris -	> Indon	esia \star 🖪	erjemahk	an pesa	an									Nonaktifi	kan untu	ak: Ingg	ris ×
	72 12			C.	70 A.												
If you have any q	is a system ge jueries we rea	enerated en Ily want to l	nail from a	in unm	anned mai	box.											
you via our 24/7 s	support at http:	y//neip.else	<u>vier.com</u>														
Article litle: Enba	ncina hambor	reinforcen	ent usina	La hosz	-clame to	increase h	ond-stres	as and slin n	esistance								
Reference: JOBE	E_100898	1 Engineeri	nan uang	i nak	s-caurip to		0110-0110.0	is and sup o	Coloride Foro								
Article Number: 1 Corresponding at	100896 utbor: Dr. Mut	star Muhtar	.9														
First author: Dr M Dear Dr. Muhtar.	luhtar Muhtar																
Your article Enha	incino bamboo	o reinforcer	ient usinc	a hose	e-clamp to	increase t	oond-stres	is and slip r	esistance v	will be pub	lished in Jou	rnal of Bu	lding Engi	ineerina.			
To track the statu	is of your artic	le througho	ut the put	licatior	n process,	please use	e our artic	le tracking :	service:					AUD 000 A U			
https://authors.els	sevier.com/tra	eking/artiel	e/details.c	lo?aid=	100896&ji	d=JOBE&s	sumame=	Muhtar									
For help with artic	cle tracking: <mark>h</mark>	ttp://help.el	sevier.com	n/app/a	inswers/de	itail/a id/9	0										
Yours sincerely,																	
Elsevier Author S	Support																
HAVE A QUERY?	?			and all the													
HAVE A QUERY? We have 24/7 sup http://help.elsevie	? pport to answ ar.com	er all of you	ir queries	quickly													
HAVE A QUERY We have 24/7 sup http://help.elsevie UNRIVALLED dis	? pport to answ ar.com ssemination fo	er all of you er your work	ir queries	quickly	ra than 15	million m	unteko oraja	TID LEADE O	(ScienceD	inset rana	ian from oria	nliple rop	aarahara	hanlihmar	n nenfer	esimal	
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en	? pport to answ ar.com ssemination fo e is published, isures that you	er all of you or your work it is made ur paper rea	r queries accessible aches the	quickly e to mo right au	re than 15 udience, w	million mo herever th	onthly uniq ey may be	que users of e on the glo	f ScienceD be, and tha	irect, rang at your res	ing from scie earch makes	ntists, res the great	earchers, est impact	healthcar possible.	e profes	ssionals	s and
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This on > Find new resea	? pport to answ ar.com ssemination fo a is published, isures that you arch yourself a	er all of you or your work it is made ur paper rea it: <u>www.scie</u>	ir queries accessible aches the incedirect	quickly e to mo right au .com	re than 15 udience, w	million mo	onthly uniq ey may be	que users of e on the glo	f ScienceD be, and tha	irect, rang al your res	ing from scie earch makes	ntists, res the great	earchers, est impact	healthcar Lpossible.	e profes	ssionals	s and
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This on > Find new resea SENDER INFOR This e-mail has b	? pport to answ ar.com ssemination fo is published, isures that you arch yourself a MATION teen sent to yo	er all of you or your work it is made ar paper rea at: <u>www.scir</u> ou from Els	r queries accessible aches the ancedirect	quickly e to mo right au .com	re than 15 udience, w e Boulevar	million me herever the	onthly uniq ey may be rd Lane. K	que users ol e on the glo Gdinaton, C	f ScienceDi be, and tha bxford, OX5	irect, rang at your res 5 1GB, Uni	ing from sole earch makes led Kinadom	ntists, res the great	earchers, est impact	healthcar possible.	e profes	ssionals	s and
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en > Find new resea SENDER INFOR This e-mail has b folders), please a	? pport to answ ar.com seemination fo b is published, isures that you arch yourself a cMATION ween sent to you add <u>Article_Str</u>	er all of you or your work it is made ar paper rea ar paper rea bu from Els bu from Els	r queries accessible accession acces	quickly e to mo right au .com ted, Thi your a	re than 15 Idience, w e Boulevar ddress bo	million mo herever the d, Langfor ok or safe	onthiy uniq ey may be rd Lane, K senders li	que users ol e on the glo Sidlington, C ist.	f ScienceD be, and tha bxford, OX5	irect, rang at your res 5 1 GB, Uni	ing from scie earch makes ited Kingdom	ntists, res the great	earchers, est impact e delivery	healthcar Loossible. To your ir	e profes nbax (no	ssionak of bulk c	s and or jun
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en > Find new resea SENDER INFOR This e-mail has b folders), please a PRIVACY POLIC Please read our p	? pport to answ ar.com ssemination for 5 published, issures that you arch yourself a cMATION ween sent to you add <u>Article_Str</u> 27 privacy policy.	er all of you or your work it is made ar paper rea ar paper rea at <u>www.scie</u> bu from Els	r queries accessible accessible aches the <u>incedirect</u> avier Limi	quickly e to mo right au .com led, Thi your a	udience, w e Boulevar ddress boi	million mc herever th d, Langför ak or safe	onthly uniq ey may be rd Lane, K senders li	que users of e on the glo Gdlington, C	f ScienceD be, and tha by ford, OX5	irect, rang at your res 5 1GB, Uni	ing from scie earch makes iled Kingdom	ntists, res the great . To ensur	earchers, est impact e delivery	healthcar possible. to your ir	e profes abox (ne	ssionak of bulk (s and or jun
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en > Find new resea SENDER INFOR This e-mail has b folders), please a PRIVACY POLIC Please read our p http://www.elsevie	? pport to answ ar.com ssemination for b s published, issures that you arch yourself a arch yo	er all of you or your work it is made ar paper rea at <u>www.scia</u> bu from Els <u>bu from Els</u> <u>ypolicy</u>	ir queries accessible aches the <u>incedirect</u> avier Limi <u>ier.com</u> to	quickly e to mo right au .com led, Thi i your a	Jdience, w e Boulevar ddress boi	million mo herever th d, Langfor ok or safe	onthly uniq ey may be rd Lane, K senders li	que users of e on the glo Gdlington, C ist	f ScienceD be, and tha bxford, OX5	lirect, rang at your res 5 1 GB, Uni	ing from scie earch makes ited Kingdom	ntists, res the great	earchers, est impact e delivery	healthcar possible. to your ir	e profes nbox (no	ssionak of bulk c	s and or jun
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en > Find new resea SENDER INFOR This e-mail has b folders), please a PRIVACY POLIC Please read our p http://www.elsevie [T-10b-20150414]	? pport to answ ar.com ssemination fo is published, isures that your arch yourself a arch yourself a arch yourself a arch yourself a stanticle_Stanticle arch yourself a com/privacy policy.	er all of you or your work it is made ar paper rea it: <u>www.scie</u> ou from Els atus@elsav ypolicy	r queries accessible aches the <u>incedirect</u> evier Limit	quickly e to mo right au .com led, Thi your a	Jdience, w e Boulevar ddress bol	million mc herever th d, Langför ok or safe	onthly uniq ey may be rd Lane, K senders li	que users ol e on the glo Gdlington, C st.	f ScienceD be, and tha bxford, OX5	ireet, rang at your res 5 1GB, Uni	ing from sole earch makes ited Kingdom	ntists, res the great	earchers, est impact	healthcar possible. to your ir	e profes nbox (no	ssionak of bulk (s and
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en > Find new resea SENDER INFOR This o-mail has b folders), please a PRIVACY POLIC Please read our p http://www.elsevie [T-10b-20150414	Pport to answ ar.com asemination for a is published, isures that you arch yourself a and yourself a and Article_Sta add Article_Sta add Article_Sta add Article_Sta add Article_Sta add Article_Sta	er all of you or your work it is made ar paper rea bu from Els atus@elsav ypolicy	ir queries accessibili aches the <u>incedirect</u> avier Limi <u>ier.com</u> to	quickly e lo mo right au .com ted, Thi	, idience, w e Boulevar ddress bol	million mo herever th d, Langfor ok or safe	onthly uniq oy may be rd Lane, K senders li	que users ol e on the glo Gidlington, C Sit.	f ScienceD bo, and tha bxford, OX5	irect, rang al your res 5 1GB, Uni	ing from scie earch makes ited Kingdom	nlists, res the great	earchers, est impact e delivery	healthear possible. to your ir	e profes nbox (no	ssionals	s and or jun
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en > Find new resea SENDER INFOR This e-mail has b folders), please a PRIVACY POLIC Please read our p http://www.elsevie [T-10b-20150414	P port to answer arcom ssemination for b is published, issues that you arch yourself a MATION ween sent to you add <u>Article_Sta</u> arch yourself a mathematical states arch yourself arch yourself arch yourself arch yourself arch yourself ar	er all of you ir your work it is made ir paper rea it: <u>www.scie</u> ou from Els <u>atus@elsav</u> ypolicy uskan	ir queries accessible aches the <u>incedirect</u> evier Limi <u>ier.com</u> to	quickly i to mo right au .com led, Thi	Idience, w e Boulevar ddress boi	million mo herever the d, Langfor ok or safe	onthly uniq ey may be rd Lane, K senders li	que users ol e on the glo Gdlington, C St.	f ScienceD be, and tha bxford, OX5	ireet, rang at your res 5 1 GB, Uni	ing from scie earch makes ited Kingdom	ntists, res the great	earchers, est impact	healthear I possible.	e profes ,	əsionalı	s and
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This en > Find new resea SENDER INFOR This e-mail has b folders), please a PRIVACY POLIC Please read our p http://www.elsevie [T-10b-20150414	? pport to answe ar.com ssemination for a is published, isures that your arch yourself a cMATION been sent to you add <u>Article_Sta</u> cy privacy policy. er.com/privac; b] Ter	er all of you ir your work it is made ir paper rea it: <u>www.scia</u> bu from Els <u>tus@elsev</u> ypolicy uskan	r queries accessible actes the <u>incedirect</u> avier Limi <u>ier.com</u> to	quickly right au right au righ	Jdience, w e Boulevar ddress boi	million mo herever the d, Langfor ak or safe	onthly uniq ey may be rd Lane, K senders li	que users ol e on the glo Gdlington, C	f ScienceD bo, and tha bxford, OX5	ireet, rang at your res 5 1 GB, Uni	ing from scie earch makes led Kingdom	ntists, res the great	earchers, est impact	healthcar possible. to your in	e profes	asionale	s and
HAVE A QUERY? We have 24/7 sup http://help.elsevie UNRIVALLED dis When your article students. This on > Find new resea SENDER INFOR This o-mail has b folders), please a PRIVACY POLIC Please read our p http://www.elsevie [T-10b-20150414	? pport to answer.com assemination for a is published, isures that you arch yourself a arch yourself a	er all of you or your work it is made ar paper rea at you from Els atus@elsav ypolicy uskan	ir queries accessibil aches the <u>incedirect</u> avier Limi <u>ior.com</u> to	quickly right ex .com led, Thi	re than 15 Jdience, w e Boulevar ddress bol	million me herever the d, Langfor ok or safe	onthly uniq cy may be rd Lane, K senders li	que users ol e on the glo Gidlington, C st.	f ScienceD be, and tha bxford, OX5	irect, rang at your res 5 1 GB, Uni	ing from scie earch makes ited Kingdom	ntists, res the great	e delivery	healthear possible. to your in	e profes	ssionals	s and

	M Gmail	Q	Telusuri email	-	0 1	:		srotan tanomadiyala how	
(+	Tulis	÷	0 1 2 2 1		226 dari 373 🔸	¢	> s	×	81
	Kotak Masuk		Production has begun on your article [JOBE_100896 Engineering 🥦 Kotak Masuk x] in Journal of	Building		ē	Ø	0
G	Ditunda	0	n.kamaraj@elsevier.com	Kar	n, 25 Jul 2019 17.46	☆	4	:	0
>	Penting Terkirim		indonesia ▼ Terjemahkan pesan		Nonaktifkan i	untuk:	loggris	×	+
	Draf		Our reference: JOBE 100896						
۰ 🖿	Kategori		Article reference: JOBE_2019_257						
~	Selengkapnya		Article title: Enhancing bamboo reinforcement using a hose-clampto increase bond-stress To be published in: Journal of Building Engineering	s and slip resistance					
			Dear Dr. Muhtar,						
			Thank you for choosing to publish in Journal of Building Engineering. Please read this e-n	mail carefully as it conta	ins important informati	on.			
			FINALIZE PUBLISHING YOUR ARTICLE:						

: 0 4

We work hard to publish our authors' articles online as quickly and efficiently as possible, therefore processing of your accepted manuscript for publication has already begun. To ensure that we publish your article in accordance with your wishes, please now complete the forms found here:

>

http://authors.elsevier.com/authorforms/JOBE100896/2aa67577834d0de165d7477f00319454

If this link does not work, please copy the entire URL (noting that it may run on to a second line in this message) into your browser. You should log in with your Elsevier Profile credentials, which you may have already created when submitting your article.

CHECK YOUR CONTACT DETAILS:

Please check that your details listed below are correct so we can contact you if needed:

Dr. Muhtar University of Muhammadiyah Jember Jember 68121 Indonesia Phone: not available Fax: not available E-mail: <u>muhtar@ummuhjember.ae.id</u>

YOUR REFERENCE NUMBER:

Lastly, to help us provide you with the best service, please make a note of your article's reference number JOBE 100896 and quote it in all of your messages to us.

Thank you for your cooperation. Please contact us if you have any questions.

Kind regards,

Mrs. Nandhini Kamaraj Data Administrator Elsevier E-Mail: n.kamaraj@elsevier.com

HAVE QUESTIONS OR NEED ASSISTANCE?

For further assistance, please visit our Customer Support site, where you can search for solutions on a range of topics and find answers to frequently asked questions. You can also talk to our customer support team by phone 24 hours a day from Monday-Friday and 24/7 by live chat and email.

Get started here: http://service.elsevier.com/app/home/supporthub/publishing

Copyright © 2015 Elsevier B.V. | Privacy Policy http://www.elsevier.com/privacypolicy Elsevier Limited, The Boulevard, Langford Lane, Kiclington, Oxford, OX5 1GB, United Kingdom, Registration No. 1982084



≡ 🎽 Gma	il Q Telu	isuri email	•	0 #	•	Cover Mata Jacks	rstan mmadiyab er	0
Tulis	÷ 8			224 dari 373 🛛 🗸	¢	> tộ	£	101
C Kotak Masuk	Y	our article [JOBE_100896] is now available online	> Kotak Masuk x			ē	Ø	۷
★ Berbintang	E	sevier - Article Status <article_status@elsevier.com></article_status@elsevier.com>	Jum,	, 26 Jul 2019 00.26	4	*	3	0
Ditunda	in the second se	ipada saya 💌						0
Penting		🛱 Inggris 🔹 🗲 Indonesia 👻 Terjemahkan pesan		Nonaktifkan	untuk:	Inggris 1	ж	
> Terkirim	A	rticle fitle: Enhancing bamboo reinforcement using a hose-clampto increase bond-str	ess and slip resistance					+
Draf	A Jo	ticle reference: JOBE_100896 surnal title: Journal of Building Engineering						
🕨 🐌 Kategori	A	rticle Number: 100396						
∨ Selengkapnya	C Fi Fi D	presponding author: Dr. Muhtar rst author: Dr. Muhtar rst published version available online: 25-JUL-2019 Ol information: 10.1016/j.jobe.2019.100896						
	D	ear Dr. Muhtar,						

We are pleased to inform you that your article is now available online at:

https://doi.org/10.1016/j.jobe.2019.100896

You might like to bookmark this permanent URL to your article. Please note access to the full text of this article will depend on your personal or institutional entitlements. The first published version of your article is made available at an early stage to provide fast access to your article and is not intended to be the final

version of

your article. The article will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note changes to the

5

article should not be requested at this stage.

This version will be replaced by the final version as soon as this is available.

Your article can already be cited using the year of online availability and the DOI as follows: Author(s), Article Title, Journal (Year), DOI.

Once the full bibliographic details (including volume and page numbering) for citation purposes are available, you will be alerted by e-mail.

To track the status of your article throughout the publication process, please use our article tracking service:

https://authors.elsevier.com/tracking/article/details.do?aid=100896&jid=JOBE&sumame=Muhtar

Kind regards,

: 0 5

Elsevier Author Support

HAVE QUESTIONS OR NEED ASSISTANCE?

For further assistance, please visit our Customer Support site where you search for solutions on a range of topics and find answers for frequently asked questions. You can also talk to our customer support team by hone 24 hours a day from Monday-Friday and 24/7 by live chat and email. Get started at > http://jeenvice.elsevier.com

© 2019 Elsevier Ltd | Privacy Policy http://www.elsevier.com/privacypolicy.

Elsevier Limited, The Boulevard, Langford Lane, Kielington, Oxford, OX5 1GB, United Kingdom, Registration No. 1982084. This e-mail has been sent to you from Elsevier Ltd. To ensure delivery to your inbox (not bulk or junk folders), please add <u>article_status@elsevier.com</u> to your address book or safe senders list.

[T-14-20180404]





hose-clampto increase bond-stress and slip resistance is now available online, containing full bibliographic

To help you access and share this work, we have created a Share Link – a personalized URL providing **50** days' free access to your article. Anyone clicking on this link before September 20, 2019 will be taken directly to the final version of your article on ScienceDirect, which they are welcome to read or download. No sign up, registration or fees are required.

. 0 .

Your personalized Share Link: https://authors.elsevier.com/a/1ZUmd_rVfDi2SI

ENGINEERING

5

Click on the icons below to share with your network:



We encourage you to use this Share Link to download a copy of the article for your own archive. The URL is also a quick and easy way to share your work with colleagues, co-authors and friends. And you are welcome to add the Share Link to your homepage or social media profiles, such as Facebook and Twitter.

You can find out more about Share Links on Elsevier.com.

Did you know, as an author, you can use your article for a wide range of scholarly, noncommercial purposes, and share and post your article online in a variety of ways? For more information visit <u>www.elsevier.com/sharing-articles</u>.

Kind regards,

details.

Elsevier Researcher Support

Increase your article's impact

Our Get Noticed guide contains a range of practical tips and advice to help you maximize visibility of your article.

Have questions or need assistance?

Please do not reply to this automated message.

For further assistance, please visit our Elsevier Support Center where you search for solutions on a range of lopics and find answers to frequently asked questions.

You can also talk to our researcher support team by phone 24 hours a day from Monday-Friday and 24/7 by live chat and email.

© 2018 Elsevier Ltd | Privacy Policy http://www.elsevier.com/privacypolicy

Elsevier Limited, The Boulevard, Langford Lane, Kidlington, Oxford, OX5 1GB, United Kingdom, Registration No. 1982084. This e-mail has been sent to you from Elsevier Ltd. To ensure delivery to your Inbox (not bulk or junk folders), please add <u>article_status@elsevier.com</u> to your address book or safe senders list.

🔦 Balas

📫 Teruskan



. 0 4



>



Thank you for publishing with us. We look forward to receiving manuscripts from you in the future!

Sincerely,

The Researcher Engagement Team

Elsevier supports responsible sharing:

Responsible sharing in line with copyright enables publishers to sustain high quality journals and the services they provide to the research community. Find out how you can share your manuscript in Elsevier journals.

- · Find useful tools and resources: Author Resources.
- For assistance, please visit our Customer Support site, where you can search for solutions on a range of topics and find answers to frequently asked questions.



This message has been sent to multian@unnuhentae ec.id from Elsevier Communications on behalf of Elsevier Journals

In initials If you no longer wish to receive messages of this nature from us in the future, please click here. Visit the Lisovier Proference Center to manage more of your communication proferences with us. Copyright © 2010 Elsevier B.V. All rights reserved. | Elsevier Privacy Policy Elsevier B.V. Registered Office: Radarwag 20, 1043 NX Ameterdam, The Netherlands. Reg. No. 33158092 Netherlands. W/T No. NL 005033019801.

[Pesan dipotong] Lihat seluruh email



100

muhtar umj ⊲muhtar@unmuhjember.ac.ids kepada Krisna ≁



Sab, 10 Agu 2019 10.07 🛛 🛧 📫

Answers to the comments from the editors and reviewers

1. Answers to comments from the editors and reviewers for points 1 to points 14

Changes have been done according to comments from the editors and reviewers as shown in the file "Manuscript files with the changes marked".

2. Answers to comments from the editors and reviewers for points 10

The distance of hose-clamp 0 cm is bamboo reinforcement does not use hose-clamp. Fig. 5 is a preliminary study to see the effect of hose-clamp on bond-stress using cylindrical specimens with variations in the hose-clamp distance as shown in points 3.3 of the first paragraph. Whereas, for the main research using hose-clamp spacing 0 cm, 15 cm, 20 cm, and 25 cm (for reinforcing of concrete beams and the distance of 0 cm is not using hose-clamp).

Enhancing bamboo reinforcement using a hose-clamp to increase bond-stress and slip resistance

Muhtar^{a,*}, Sri Murni Dewi^b, Wisnumurti^b, As'ad Munawir^b

^aDepartment of Civil Engineering, Faculty of Engineering, University of Muhammadiyah Jember, Jember, 68121, Indonesia

^bDepartment of Civil Engineering, Faculty of Engineering, University of Brawijaya, Malang 65145, Indonesia

* Corresponding author. E-mail address: muhtar@unmuhjember.ac.id

Abstract

Bamboo can be used as reinforcement for concrete, especially in simple construction, because of its high tensile strength. Any collapse that occurs in a bamboo reinforced concrete beam is often caused by failure of the bond between bamboo and concrete. Many researchers have suggested using adhesive coatings or roughness modifications to bamboo reinforcement, but a slip failure pattern still appears. The aim of this research is to increase bond-stress and slip resistance by using a hose-clamp, and to obtain a relationship model of load vs. deflection and bond-stress vs. slip between bamboo reinforcement and concrete. The experiments use 75 mm x 150 mm x 1100 mm concrete beams. Concrete beam specimens comprise 24 bamboo-reinforced beams, one beam with 8 mm diameter steel reinforcement, and one without reinforcement. Hose-clamp spacing varies by 0 cm, 15 cm, 20 cm, and 25 cm. Beam testing uses a four-point loading method. Test results show an increase in bond-stress and flexural capacity, and reduced slip between bamboo reinforcement and concrete, solution stress are used. There are differences in the relationship of load vs. deflection and bond-stress vs. slip between bamboo reinforcement and concretes are used. There are differences in the relationship of load vs. deflection and bond-stress vs. slip between bamboo reinforced concrete beams and steel reinforcement and concrete beams.

Keywords: bond-stress, slip resistance, bamboo reinforced concrete, hose-clamp

1. Introduction

Exploiting industrial building materials with an indifference to using renewable building materials can cause permanent environmental pollution. Bamboo, as a renewable building material, can minimize energy consumption, protect non-renewable natural resources, reduce pollution and maintain a healthy environment. Bamboo is a material with an economic advantage because growth is relatively fast, allowing it to achieve maximum mechanical resistance within a few years. In addition, bamboo is very abundant in the tropics and subtropics throughout the world [1].

Bamboo can be used for concrete reinforcement for modest housing communities in areas where it is abundant, especially underdeveloped villages. However, bamboo is considered unprofitable because of the methods required to prepare it for such use. Researchers have tried to simplify bamboo treatment and eliminate operational problems in using it as the main structural component. Many of them focus on examining whether bamboo reinforcement is really cheaper than steel reinforcement, taking into account operational costs, depreciation losses, required skills, and on-the-job training needs for long-term use [2]. Other researchers discuss the feasibility of bamboo in technical, cost, durability, and other terms [3-10].

A frequent barrier to developing bamboo reinforced concrete is the failure of the bond between the bamboo reinforcement and the concrete. This occurs because of the slippery nature of the bamboo surface, and imperfect attempts to modify its roughness. Treatments to counteract the slipperiness have included soaking, drying, waterproof coating, and sprinkling with dry sand. Nevertheless, the collapse pattern is still dominated by slip failure between bamboo reinforcement and concrete. Tripura and Singh [11] recently proposed a column reinforcement technique to increase the strength and performance of bamboo reinforcement, but the user must pay attention to humidity, and bond properties need to be determined for better results.

The aim of this research is to increase bond-stress and slip resistance using a hose-clamp, and to obtain a relationship model of load deflection and bond-stress and slip between the bamboo reinforcement and the concrete.

The concept of installing a hose-clamp on to bamboo reinforcement is similar to the concept of using deformed bar reinforcement in concrete [12] as shown in Fig. 1 and Fig. 2, where there are frictional force interaction and the bearing force between bamboo reinforcement and concrete. Installing hose-clamps in this way will increase slip resistance and bond-stress. The frictional force of the bamboo reinforcement surface will be distributed on the hose-clamp that functions as a shear connector. Strengthened bamboo reinforcement using a hose-clamp is then applied to concrete beams and evaluated by flexural testing.



Fig. 1. Bamboo reinforcement with a hose-clamp



Fig. 2. The friction force and bearing force of a deformed bar [12]

2. Theory

The reinforced concrete bond is formed by the mechanism of adhesion, friction and mechanical interlock between the reinforcement and the concrete. Bond strength is strongly influenced by fracture energy [13] as well as complex interactions between local deformation, chemical adhesion, and other factors [14]. The shear forces transferred between the bamboo reinforcement and the concrete is the dominant factor after the adhesive bond. A good bond between concrete and reinforcing bamboo is essential so that the system can behave as planned, and also to fulfill the required performance of the structure in the long run. The bamboo reinforcement surface condition and the shearing surface area are important factors in the shear stress value.

Roughness modification of bamboo reinforcement is carried out by notching [15], wire and coir winding [16], the addition of hooks [17], or installation of hose-clamps [18-20]. These methods can increase the bearing capacity of a bamboo reinforcement concrete beam, but still have drawbacks, such as difficult implementation, and a notching process can weaken bamboo reinforcement. Agarwal et al. [21] conducted research on a bamboo reinforced concrete beam using waterproof coating Sikadur 32 Gel and sand. The capacity of the beam load increased by up to 29.41% for a 1.49% bamboo reinforcement area, but slip failure still occurred. Gisleiva C.S. [22] tested bamboo reinforced concrete beams using a two points load method, and showed that the beam crack occurs due to bond failure between bamboo reinforcement and concrete, followed by sliding failure and slip.

The bamboo reinforcement adhesive should also serve as an impermeable layer and sand sheathing binder to the bamboo reinforcement. Some types of adhesives that have been used include: Negrolin, Sikadur 32 Gel [1]; Sikadur-31CFN [23]; Araldite, Tepecrete P-151, Anti Corr RC, and Sikadur 32 Gel [21]; Araldite, epoxy resin, and coal tar [24]; paint and dry sand [25]; layer asphalt and sand on bamboo reinforcement [26]; asphalt layer and coir rope coiled [27]; Concresive Master Inject 1315 [28]; synthetic resin and synthetic rubber [29]; water-based epoxy coating with fine sand, water based epoxy coating with coarse sand, TrueGrip EP with coarse sand, TrueGrip BP with coarse sand, Exaphen with coarse sand, and enamel [30]; and lime water treated bamboo mat coated with epoxy and sand [31].

In the pull-out testing of concrete, the bond strength decreases as the steel reinforcement diameter increases; the deeper the embedded reinforcement steel, the higher the bond-stress value [32-33]. Javadian et al. [30] investigated bamboo pull-out, using a type of epoxy coating, to determine the bonding behavior between bamboo reinforcement and concrete. The results showed that bamboo-composite reinforcement without layers has sufficient ties with the concrete matrix, but with the epoxy base layer and sand particles provides extra protection without loss of bond strength. Where failure occurs, it is at the bond between reinforcing steel with concrete, and slippage. The pull-out testing results by Muhtar et al. [19] on bamboo reinforced concrete with Sikadur®-752 coating and hose-clamps

embedded in concrete cylinders indicated an increase of tensile stress of up to 240% compared to untreated bamboo reinforced concrete. The pattern of collapse indicates the collapse pattern of bond and concrete cone failure and Bamboo failure of a node. This shows that using a hose-clamp on bamboo reinforcement works well, with the concrete remaining attached to the bamboo reinforcement.

Installation of hose-clamps increases slip resistance along the bamboo reinforcement. The frictional force of the bamboo reinforcement surface is distributed on the hose-clamp that serves as a shear connector. The bonding stress parameter between bamboo reinforcement and concrete can be shown in flexural capacity, crack pattern, and beam failure pattern.

Hose-clamp installation on bamboo reinforcement serves as anchoring friction between bamboo reinforcement with concrete. The friction strength, τ_b of the bamboo pullout test can be calculated using Eq. (1) [30]:

$$\tau_b = \frac{P}{(2a+2b)L_a} \tag{1}$$

where P is the pullout force, (2a + 2b) is the dimension of the bamboo cross-section, and L_a is the length of bamboo surface attachment.

The bond-stress (u) of the BRC beam can be calculated by Eq. (2) and Eq. (3) [25, 34]:

$$u = \frac{V}{jd.\Sigma o} \tag{2}$$

$$jd = (d - \frac{1}{2}a) \tag{3}$$

where V is the shearing force of the beam, $\sum o$ is the circumference of the nominal surface area of the bamboo reinforcement in length units, d is the distance from the maximum press fiber to the center of the bamboo tensile reinforcement area, and a is the height of concrete stress block equivalent.

3. Materials and methods

3.1. Preparation of bamboo reinforcement.

This research uses bamboo petung (Dendrocalamus asper) between three and five years old [21], six meters long from its base. Bamboo is cut and separated according to the planned size, then soaked in water to remove the starch content for approximately 30 days. After soaking, bamboo is dried in free air for about 30 days [21, 35]. The dried bamboo is cleaned on the inner side and trimmed with a grinding machine to the required shape for bamboo reinforcement measuring 7 x 10 mm², 10 x 10 mm² and 15 x 15 mm². The number of bamboo reinforcement nodes used varies between two and three pieces.

3.2. The waterproof coating Sikadur[®]-752 and installation of hose-clamp.

After the bamboo reinforcement preparation process is complete, the next step is the waterproof coating and installation of hose-clamps. The waterproof coating used was Sikadur[®]-752, and the coating was carried out twice. Sikadur[®]-752 is applied to the bamboo reinforcement to prevent water absorption; the effectiveness and durability of Sikadur[®]-752 adhesive require further research. The specification of Sikadur[®]-752 is shown in Table 1. Hose-clamps installation is carried out after the first stage Sikadur[®]-752 waterproof coating is dry. The second layer of waterproofing is applied with the aim of making the first stage impermeable, and of strengthening the bond between hose-clamps and bamboo reinforcement. The hose-clamp used is a ³/₄" diameter stainless steel unit made in Taiwan specifications are not available. The distance variation of the hose-clamp setting is 0 cm, 15 cm, 20 cm, and 25 cm. To overcome bamboo node disturbance, hose-clamps are installed in one of two ways, either by stretching the hose-clamp bolt and inserting directly from the tip of the bamboo reinforcement, or by opening the hose-clamp bolt first and installing the unit using a screwdriver. Nearly one-third of the surface of bamboo reinforcement is slippery. To increase its roughness, sand is sprinkled on [30] after the Sikadur[®]-752 waterproof coating is half-dry. The sand used is fine volcanic dust sand from Raung Mountain, Jember, Indonesia, which contains particles of iron. The process of preparing bamboo, including waterproof coating and sprinkling sand, up to hose-clamp installation, is shown in Fig. 3 and Fig. 4.

Table 1	The s	pecification	of Sikadur®	-752

Components	Properties
Aspect	Yellowish
Mix density	Approx. 1.08 kg/l
Mix ratio, by weight/volume	2:1
Pot life 30°C	35 minutes
Compressive strength	620 kg/cm ² at 7 days
	640 kg/cm^2 at 28 days
Tensile strength	270 kg/cm ² at 28 days
Bond strength, to concrete	>20 kg/cm ² (concrete failure, over mechanically prepared
	concrete surface)
Flexural strength	400 kg/cm ² at 28 days
Modulus of elasticity	10,600 kg/cm ²



Fig. 3. Tidying a bamboo bar with a grinding machine



Fig. 4. Processing a waterproof coating, a sand coating, and a hose-clamp installation

3.3. Pull-out tests

The dimensions of bamboo reinforcement used in the pull-out tests are 15 mm x 15 mm x 400 mm, while the size of the concrete cylinder is a diameter of 150 mm and a length of 300 mm. A bamboo reinforcement is inserted into the middle of a concrete cylinder with a depth of 200 mm. Specimens are tested after 28 days; 15 test pieces were made, with five treatments, namely (a) normal, (b) hose-clamp with span 10 cm, (c) Sikadur[®]-752, (d) Sikadur[®]-752 and hose-clamp with span 15 cm, and (e) Sikadur[®]-752 and hose-clamp with span 20 cm. The purpose of the treatment on the specimen is to increase the bond-strength between bamboo and concrete. Specimen details from the pull-out test are shown in Fig. 5, while the manufacture of specimens and pull-out test settings are shown in Fig. 6.



Fig. 5. Specimen details of the pull-out test



Fig. 6. Manufacture of specimens and pull-out test settings

3.4. Testing methods

The mix design of normal concrete for this research comprised Portland Pozzolana Cement (PPC), sand, coarse aggregate, and water with a proportion of 1:1.8, 1:2.8, 2:0.52. Sand and gravel are from the Malang area. The cylinder specimen measured 150 mm diameter and 300 mm height. A universal testing machine (UTM) with 2000 kN capacity was used for a compression test. The values of the concrete compressive strength test and the bamboo tensile strength test were used as the basis for the theoretical calculation of the beam.



The beam test specimen comprised 26 pieces with a size of 75 mm x 150 mm x 1100 mm, as shown in Fig. 7, consisting of 24 pieces of the bamboo reinforced concrete beam (BRC), one steel reinforced concrete beam (SRC), and one concrete beam without reinforcement (PC). Bamboo reinforcement is installed as tensile reinforcement with a

variation of reinforcement area of 140 mm², 200 mm², and 450 mm². The steel bars used are 8 mm in diameter with an $A_s = 100.48$ mm² reinforcement area. The use of two bars of 8 mm diameter is not equivalent to the bamboo reinforcement area used; if equalized it must be made in non-dimensional conditions, but this is not fully suitable because its behavior will not be the same if it has reached post-crack. This requires further research.

The flexural beam test is carried out using a four-point technique [36]. There are two points loads with spacing $\frac{1}{L}$ from the beam support, using a WF load spreader. The strain gauge is mounted on bamboo reinforcement $\frac{1}{L}$ from the beam support. The strain gauge is connected to the digital strain meter. The deflection that occurs in the beam is detected using LVDT (linear variable displacement transducers) $\frac{1}{L}$ from the beam support. A hydraulic jack is used for beam loading and 200 kN load cell connected to the load indicator. Load indicator readings are used as hydraulic jack controllers, deflection readings, and strain readings, according to load control methods. After the test beam reaches its ultimate load, readings are taken according to the deflection control method. The pattern of collapse is observed and identified through cracks that occur, starting from the first crack until the beam collapses. The test equipment settings and load scheme are shown in Fig. 8.



Fig. 8. The setting of the flexural beam test

4. Results and Discussion

4.1. Material test and pull-out test

The bamboo tensile test returned an average tensile stress of 126.68 N/mm² and an average strain of 0.0074. The average of the modulus of bamboo elasticity is calculated based on the formula $E = \sigma/\epsilon$, and 17235.74 MPa was obtained. Modulus of steel elasticity was 207735.92 MPa. In bamboo tensile testing, the majority of failures of bamboo reinforcement occur at the point of the bamboo node as shown in Fig. 9, so that the modulus of elasticity is taken as an average test result of bamboo reinforcement with nodes and without nodes. Fig. 10 and Fig. 11 show a graph of the stress-strain relationship of bamboo and steel, a graph of the stress-strain relationship of bamboo tends to be linear until fracture stress occurs, so there are difficulties in determining the yielding point, especially if bamboo has been used as concrete reinforcement. So in this study, the method for determining the yield point of bamboo reinforcement in the concrete beam was based on ASTM E2126-09 [37] scope 1.2, which is for specimens constructed from wood or metal framing, braced with solid sheathing. Compression tests were carried out in accordance with ASTM C 39 [38] after 28 days of concrete age. The compressive strength of the average cylinder is 31.31 MPa and the average weight of the cylinder is 125.21 N.



Fig. 9. The pattern of failure in bamboo reinforcement





Fig. 10. The stress-strain relationship of normal bamboo reinforcement

Fig. 11. The stress-strain relationship of steel reinforcement

The data from the pull-out test results of bamboo reinforcement, treated with waterproof coating Sikadur[®]-752, sand and hose-clamp rings embedded in concrete cylinders, showed an increase in bond-stress of 214% and 200% compared to bamboo without treatment, with a distance of hose-clamps of 15 cm and 20 cm, respectively; with the loading rate, respectively 39.5 kN and 37.5 kN. For bamboo reinforcement without waterproof coating Sikadur[®]-752 and sand, but using hose-clamps with a distance of 10 cm, this increased by 8%, whereas bamboo reinforcement with waterproof coating Sikadur[®]-752 and sand without hose-clamps increased by 125% compared to untreated bamboo, as shown in Fig. 12.



Fig. 12. Variation of the bamboo bond-stress



Fig. 13. The failure mode of the pull-out test

Test specimens with waterproof coating Sikadur[®]-752, sand, and hose-clamps showed a collapse pattern of "bond and concrete cone failure" as shown in Fig. 13a. This shows that the waterproof coating Sikadur[®]-752 and the hoseclamps on the bamboo reinforcement have worked well, as indicated by the concrete attached to the bamboo reinforcement. Test specimens with waterproof coating Sikadur[®]-752 and sand, but without hose-clamps, show a collapse pattern of "bond-slip failure", but have a fairly high bond strength, as shown in Fig.13b. Whereas the specimen with hose-clamps without waterproof coating Sikadur[®]-752 or sand show a collapse pattern of the "bondslip failure" with bond-stress similar to that of untreated bamboo reinforcement. This shows that there is an action of absorbing water between bamboo reinforcement and concrete. When the concrete is wet, the bamboo reinforcement absorbs water so that the bamboo reinforcement swells. When the concrete is dry, the water in the bamboo reinforcement is absorbed by the concrete, so that the bamboo reinforcement shrinks and the hose-clamp becomes loose. This causes a slip to occur and the hose-clamp has no effect on bond-stress. The pattern of the collapse is shown in Fig. 13b.

The analysis of the test results and the pattern of collapse shows that the use of waterproof coating is absolutely

necessary; the installation of hose-clamps on bamboo reinforced concrete without waterproof coating has no significant effect.

4.2. The flexural capacity of the bamboo reinforced concrete beam

Theoretical analysis of beam flexural capacity is based on Ghavami (2005) [1]. From the analysis of stress and strain distribution of flexural beam elements, the balance between the concrete compressive force (C) and the tensile force (T) must be fulfilled. The tensile strength of bamboo reinforcement (T) was obtained by multiplying bond-stress from the pull-out test results by the shear area of bamboo reinforcement; this is because, based on the results of the study, the collapse of bamboo reinforced concrete was caused by the loss of bond between bamboo reinforcement and concrete. Data from theoretical calculations and BRC beam experimental results are shown in Table 2.

The initial crack of BRC beams from theoretical calculations occurred at a load of 6.87 kN, while ultimate loads occurred at 29.62 kN, 33.73 kN, and 45.27 kN respectively on BRC beams with bamboo reinforcement areas of 140 mm², 200 mm², and 450 mm². The average load of the initial crack of the experimental results occurs at a load of 7.35 kN. Fig. 14 shows the average initial crack load and the average ultimate load of a BRC beam from theoretical calculations and experimental results. The average ultimate load of the experimental results is 90% of the ultimate load resulting from the theoretical calculations. This is one solution to the problem of the low capacity of bamboo reinforced concrete beams, as reported by several previous researchers. They concluded that the flexural capacity of bamboo reinforced concrete beams reached only 56% of its capacity if the tensile strength of bamboo was full [17], only 29% to 39% of the capacity of steel reinforced concrete beams with the same reinforcement dimensions and width [39], and only 35% of steel reinforced concrete beams at the same strength level [40].



Fig. 14. The ultimate load of theoretical and experimental results of the BRC beam



Fig. 15 shows a comparison of the ultimate load of BRC beams and SRC beams, based on reinforcement area variation and hose-clamp distance. BRC beams with a reinforcement area of 450 mm² have the highest ultimate load for all variations in the distance of the hose-clamps. Whereas when viewed from the variation in the distance of the hose-clamps, BRC beams with a distance of 20 cm hose-clamps have the highest ultimate load, 33.25 kN. BRC beams with a ratio of 4% bamboo reinforcement area exceed the ultimate load of steel reinforced SRC beams by up to 38.54% with a steel reinforcement area ratio of 0.89%.

The results of the analysis of variance on all data from the flexural test show the non-significant effect of hoseclamps on the beam capacity, whereas from the pull-out test results, as shown in Fig. 12, the effect of hose-clamps is significant. This indicates that: (1) the distance of the installation of the hose-clamps has not been optimum or is still too tight for flexural tensile reinforcement. Installation of tight hose-clamps will reduce the elastic properties of bamboo and bamboo reinforcement becomes more rigid. Bamboo has high tensile strength in the direction of the fiber (longitudinal direction), but is weak in the transverse direction, so that when receiving a flexural tensile force, there will be a concentration of stress, and bamboo reinforcement ruptures, especially at the point of the bamboo node and the position of the hose-clamp; (2) installation of effective hose-clamps if used on pure tensile elements, such as truss elements or as the length of distribution (L_d) for bamboo reinforcement; (3) waterproof coating Sikadur[®]-752 and sand have a significant effect on bond-stress. This is indicated by the ultimate load of BRC-s0 beam approaching the ultimate load of BRC-s1, BRC-s2, and BRC-s3 beams. The installation of hose-clamps without waterproof coating treatment does not have an effect on the bond-stress or beam capacity. The installation of hose-clamps as flexural tensile reinforcement needs further research, with the hose-clamps distance larger and more effective.

Table 2Flexural beam test results

			Theoretical calculations				Flexural test results							
No S	Specimens	code		Ultimate load base on the tensile strength of bamboo (kN)	Ultimate load base on the shear area of bamboo reinforcement (kN)	First crack load (kN)	Average first crack load (kN)	Failure load (kN)	Average failure load (kN)	Deflection at failure (mm)	Average deflection at failure (mm)			
1	BRC - s0	A1B1	6 97	11 20	20.61	8.50	° 25	22.00	21.75	12.10	12.40			
2	$As = 140 \text{ mm}^2$	A1B1	0.87	11.39	29.01	8.00	8.23	21.50	21.75	12.69	12.40			
3	BRC - s1	A1B2	6.87	(07 11 20	20 (1	7.00	6.75	21.00	18 50	6.08	C 40			
4	$As = 140 \text{ mm}^2$	A1B2	0.87	11.59	29.01	6.50		16.00	18.50	6.72	0.40			
5	BRC - s2	A1B3	6.87	11 39	29.61	6.00	6.25	22.00	22.25	9.09	9.20			
6	$As = 140 \text{ mm}^2$	A1B3	0.07	11.57	29.01	6.50	0.25	22.50	22.23	9.31	9.20			
7	BRC - s3	A1B4	6 87	11 39	29.61	8.00	7 75	19.50	20.75	10.21	11 57			
8	$As = 140 \text{ mm}^2$	A1B4	0.8/	11.57	29.01	7.50	1.15	22.00	20.75	12.92	11.57			
9	BRC - s0	A2B1	6 97	6.87	6 87	15.86	33 73	6.50	6.75	26.50	27.75	10.21	11 17	
10	$As = 200 \text{ mm}^2$	A2B1	0.07	10.00	55.75	7.00	0.70	29.00		12.12				
11	BRC - s1	A2B2	6 87	15.86	33.73	6.50	7.00	33.00	30.75	14.84	13.39			
12	$As = 200 \text{ mm}^2 \qquad A2B2$				7.50		28.50		11.94					
13	BRC - s2	A2B3	6.87	6 87	6 87	6.87	15.86	33.73	6.50	6.75	31.00	31.50	13.25	13.50
14	$As = 200 \text{ mm}^2$	A2B3				7.00	0.70	32.00	51.00	13.74				
15	BRC - s3	A2B4	6.87	6.87	6.87	15.86	33.73	8.50	8.00	29.50	29.00	9.66	10.80	
16	$As = 200 \text{ mm}^2$	A2B4				7.50		28.50		11.94				
17	BRC - s0	A3B1	6.87	32.19	45.27	8.50	8.25	31.50	30.25	10.92	11.41			
18	$As = 450 \text{ mm}^2$	A3B1				8.00	0.20	29.00		11.90				
19	BRC - s1	A3B2	6.87	32.19	45.27	7.00	7.25	31.00	32.00	12.18	12.60			
20	$As = 450 \text{ mm}^2$	A3B2				7.50		33.00		13.02				
21	BRC - s_2	A3B3	6.87	32.19	45.27	8.00	7.75	33.50	33.25	14.69	12.01			
22	$AS = 450 \text{ mm}^2$	A3B3				7.50	1.10	33.00		9.32				
23	BRC - s_3	A3B4	6.87	32.19	45.27	7.50	7.50	29.50	29.75	7.61	9.15			
24	$Ab = 450 \text{ mm}^2$	A3B4				7.50		30.00		10.69				
25	$As = 100,48$ mm^2	SRC	6.51	16.63		10.00	10.00	24.00	24.00	6.33	6.33			
26	РС	PC	6.39	9.42		8.00		8.00		1.29				

4.3. The load-deflection relationship model of the bamboo reinforced concrete beam

The pattern of the load-deflection relationship between BRC and SRC beams is strongly influenced by the mechanical properties of bamboo and steel reinforcement materials. The different characteristics of stress and strain in bamboo and steel are the dominant factors in determining the characteristics of load-deflection relationships. On the stress-strain characteristics of bamboo, it does not have a long initial melting point. This means the service load range point or the proof bond strength point cannot be directly determined. The relationship between load and deflection was carried out on BRC beams with a bamboo reinforcement area of 450 mm² with a hose-clamp distance of 0 cm, 15 cm, 20 cm, and 25 cm. This is because it has the highest ultimate load and good data consistency.

Fig. 16 and Fig. 17 show the differences in the behavior of load-deflection and load-strain relationships of BRC and SRC beams. The BRC beam has a much higher deflection. This shows higher energy absorption, but lower stiffness. The SRC beams can directly determine the initial yield point of reinforcement. A graph of the load-deflection relationship of the SRC beam shows the elastic area or friction bond limit (I), elasto-plastic (II), and plastic (III), while the BRC beam does not clearly show plastic areas – the BRC beam load-deflection graph tends to be linear. However, the crack moment (M_{cr}), which is the point of friction bond limit, can be known directly through the

initial crack that occurs.



Fig. 16. Load-deflection relationship of BRC beams



Fig. 17. Load-strain relationship of BRC beams

The service load range is determined based on ASTM E 2126-09 [37], that is by drawing a vertical line through the $0.4P_{ultimate}$ line meeting with a $0.8P_{ultimate}$ horizontal line. From the analysis results, the average value of $P_{service}$ load is 18.79 kN or about 60% of $P_{ultimate}$. While the elastic range or friction bond limit points using Eq. (4) [33]:

$$\frac{P_{cr}}{P_{ultimate}} = \overline{R}u - 2.3(\sigma) = 20.08\% \approx 20\%$$
⁽⁴⁾

Table 3	
Load-displacement relationship calculation	data.

		Theoretical calculations			Flexural test results				
Specimens / Code	No	First crack load (kN)	Ultimate load (kN)	First crack load, P _{cr} (kN)	Failure load, P _{ultimate} (kN)	Deflection at failure (mm)	$P_{cr}/P_{ultimate}$ (%)		
(a) BRC-s0 / A3B1	1	6.97	22.10	8.50	31.50	10.92	26.98		
	2	0.8/	32.19	8.00	29.00	11.90	27.59		
(b) BRC-s1 / A3B2	1	(07	32.19	7.00	31.00	13.02	22.58		
	2	0.8/		7.50	33.00	12.18	22.73		
(a) DDC a^2/A^2D^2	1	6.87	32.19	8.00	33.25	14.69	23.88		
(C) BRC-S2 / A5B5	2			7.50	33.00	9.32	22.73		
(1) DDC -2 / A2D4	1	(07	22.10	7.50	29.50	7.61	25.42		
(d) BRC-\$3 / A3B4	2	0.8/	32.19	7.50	30.00	10.69	25.00		
Mean values (Ru)			7.69	31.31	11.29	24.61		
Standard deviation	(σ)			0.46	1.73		1.97		





Fig. 18. The idealization of the load- deflection relationship model of BRC beam

Fig. 19. The difference in stiffness between the BRC beam and the SRC beam

Table 3 shows that the lowest elastic value, 22.58%, occurred in the BRC-s1 beam, the highest, 27.59%, in the BRC-s0 beam. The average value of the elastic range is 24.61% of the ultimate load. From the calculation using Eq. (4), the value of the elastic limit is obtained by 20% of the ultimate load. The elastic limit on the SRC beam is 41.67%

of the ultimate load. It can be concluded that the point of the elastic limit is 20% of the ultimate load, and the service load range is 60% of the ultimate load. The idealization of the BRC beam load-deflection relationship model is shown in Fig. 18.

In Fig. 19, if horizontal lines are drawn at service limits $P_{service}$, and linear lines are parallel to the SRC beam loaddeflection diagram, it will be seen that the BRC beam stiffness is much lower than SRC beam stiffness. The average value of the BRC beam stiffness was lower – 43.92% – compared to the SRC beam. Whereas if we take when the initial crack load of the SRC beam, or $0.4P_{ultimit}$, is obtained, the BRC beam stiffness is lower than 75% of the SRC beam stiffness, as shown in Fig. 19. This is a weakness of the BRC beam that needs to be considered in future studies. The principle of the theory of confined concrete and shear reinforcement can be a solution to overcome the low rigidity of the BRC beam.

4.4. The bond-stress of flexural beam.

Measurements and observations of slip (*s*) are carried out from when the initial crack occurs until the beam has collapsed. The measurement of slip (*s*) is taken in two ways, namely direct measurement through a strain gauge attached to a bamboo reinforcement for elongation of bamboo reinforcement (e_{bo}), and measurement through force analysis or curvature moment for elongation of the concrete (e_{co}). The readings from the strain gauge installed on bamboo reinforcement can still be carried out even though the concrete has been cracked, because when the concrete cracked, the bamboo reinforcement was still not yielding or was still in an elastic condition. Direct measurement through strain gauge and measurement through force analysis is carried out as control and comparison. Slip (s_o) at the point where the bond-stress occurs is calculated based on Eq. (5) [41].

$$S_o = e_{bo} - e_{co} \tag{5}$$

where e_{bo} = elongation of bamboo reinforcement, and e_{co} = elongation of concrete. The elongation of concrete (e_{co}) is calculated using Eq. (6) [41].

$$e_{co} = e_{c,co} + e_{c,bo} \tag{6}$$

where $e_{c,co}$ = elongation of concrete due to the compressive force, and $e_{c,bo}$ = elongation of concrete due to bond force.

The purpose of installing hose-clamps on bamboo reinforcement is to increase slip resistance between bamboo and concrete reinforcement. The test results and the calculations of bond-stress and slip can be seen in Table 4 and Table 5. Fig. 20 shows the relationship between bond-stress and slip in the BRC beam, divided into two stages. The first is the linear elastic stage, where the linear line curve shows the full elastic behavior of the BRC beam. The shear force that occurs on the reinforcement surface of bamboo is transferred to concrete. The maximum tensile stress on the beam is smaller than the flexural tensile strength, or smaller than the concrete collapse modulus. The second stage is a combination of elasto-plastic and plastic stages; this is consistent with the characteristics of the stress-strain of bamboo reinforcement which does not have a long yielding point, as shown in Fig. 10. This stage is the beginning of the micro slip of bamboo reinforcement and concrete.



Fig. 20. Relocation bond-stress and slip on a BRC beam

Fig. 21. The relationship of bond-stress and slip on a BRC beam

The bond-stress of bamboo reinforcement starting to work up to ultimate bond-stress. The tensile stress that occurs is completely retained by bamboo reinforcement with its friction strength. Bond-stress increases with increasing slip resistance force. Likewise, the cracks increase and widen as the slip increases. The ultimate tension occurs when the maximum slip occurs on the bamboo reinforcement. The ultimate bond-stress occurs when the maximum slip occurs on the bamboo reinforcement.

From Table 5, the ratio between the friction bond limit and ultimate bond strength (u_f/u_u) ranges from 21% to

27%. While the bond-stress (*u*) from the friction bond limit up to ultimate bond strength can be approximated by the Eq. (7), with the limit of $s_y < s_o \le s_u$, where s_y is slip on the initial crack of the beam, and s_u is the slip at the ultimate load as shown in Fig. 21.

$$u = 0.027s_o + 0.026 \tag{7}$$

Table 4

Bond-stress and slip of the flexural beam test.

	Sample no	Theoretical calculations				Flexural						
Specimens / Code		First crack load (kN)	Ultima te load (kN)	First crack load (kN)	Average first crack load (kN)	Failure load (kN)	Average failure load (kN)	Deflectio n at failure (mm)	Average deflection at failure (mm)	bond- stress (MPa)	Slip, s _o (mm)	
(a) BRC-s0	a) BRC-s0 1	6.87	32 10	8.50	8 25	31.50	30.25	10.92	11.41	0.31	9.05	
/ A3B1	2	0.87	32.19	8.00	8.23	29.00		11.90				
(b) BRC-s1	BRC-s1 1	6 87	32 10	7.00	7 25	31.00	32.00 13. 12.	13.02	12.60	0.33	10.85	
/ A3B2	2	0.87	52.19	7.50	1.20	33.00		12.18				
(c) BRC-s2	1	6.87	6 87 22	32 10	8.00	8.00	33.50	22.25	14.69	12.01	0.22	0.76
/ A3B3	2		32.19	7.50	8.00	33.00	35.25	9.32	12.01	0.55	9.70	
(d) BRC-s3 1 / A3B4 2	1	6 97	6.07 22.10	7.50	7.50	29.50	29.75	7.61	9.15	0.30	10.12	
	2	0.87	32.19	7.50	7.50	30.00		10.69				
(e) SRC	1	6.51	16.63	10.00	10.00	24.00	24.00	6.33	6.33	0.24	12.53	

Table 5

Bond-stress calculation.

	Theoretical of	calculations					
Specimens/Code	First crack load (kN)	Ultimate load (kN)	First crack load (kN)	Failure load (kN)	Flexural beam bond- stress, u_u (MPa)	u _f (MPa)	u_f/u_u (%)
(a) BRC-s0 / A3B1	6.87	32.19	8.50	31.50	0.311	0.079	25
	6.87	32.19	8.00	29.00	0.306	0.074	24
(b) BRC-s1 / A3B2	6.87	32.19	7.00	31.00	0.326	0.069	21
	6.87	32.19	7.50	33.00	0.321	0.064	20
(c) BRC-s2 / A3B3	6.87	32.19	8.00	33.50	0.331	0.079	24
	6.87	32.19	7.50	33.00	0.321	0.084	26
(d) BRC-s3 / A3B4	6.87	32.19	7.50	29.50	0.296	0.074	25
	6.87	32.19	7.50	30.00	0.291	0.079	27
Mean values ($\overline{R}u$)					0.313		24
Standard deviation (σ)					0.01		2.42
(e) SRC	6.51	16.63	10.00	24.00	0.24		

4.5. The relationship model of bond-stress and slip in the bamboo reinforced concrete beam

Fig. 22 shows the bond-stress and slip relationship of BRC beam with a hose-clamp on bamboo reinforcement, where point a is the friction bond limit (u_f) , and d is the ultimate bond strength (u_u) . The ratio average of the friction bond limit (u_f) with the ultimate bond strength (u_u) of the BRC beam is 24%, and a minimum ratio of 21% occurs on the BRC-s1 beam, while a maximum ratio of 27% occurs on the BRC-s3 beam. The proposed u_f/u_u ratio is taken with Eq. (8) [33].

$$\frac{u_f}{u_v} = \overline{R}u - 2.3(\sigma) = 18.43\% \approx 20\%$$
(8)

The bamboo reinforced concrete beam (BRC) in Fig. 17 and Fig. 20 does not show elasto-plastic or plastic boundaries, so the boundaries point of proof bond strength (u_{pr}) and bond-stress at pre-cracking become nothing. This is in accordance with the stress-strain characteristic of bamboo reinforcement, that no length yield region occurs as it does in steel reinforcement. Thus, the region of post-friction bond limit (u_f) is a linear line until reaching ultimate bond strength (u_u) . The value of the friction bond limit (u_f) point up to the ultimate bond strength (u_u) point is estimated at about 80%. If based on ASTM E 2126-09 [37], which sets out how to determine the yielding point of a wooden structure, then u_u is taken at $0.8u_{peak}$, and the ultimate bond strength (u_u) point is estimated at about 60%. Diab et al. [33], with a steel pull-out test, proposed the u_f/u_u ratio for the point (a) friction bond limit (u_f) of 50%, (b) proof bond strength (u_{pr}) of 60%, and (c) bond-stress at pre-cracking by 70%.



Fig. 22. The idealization of the bond-stress and slip relationship of the BRC beam

The difference between the relationship diagram of bond-stress and slip and the friction bond limit value (u_f) is far enough between the BRC and the SRC beam. This is due to a faster initial crack in the BRC beam. Initial cracks occur faster due to several reasons, including (1) the presence of microcracks around hose-clamps caused by air bubbles during the cement hydration process, (2) shrinkage occurring in bamboo reinforcement because the defects are not coated with a waterproof coating, especially during execution, and (3) the modulus of elasticity of bamboo is lower than concrete. Points (1) and (2) above are possible if work is not carried out under strict supervision.

4.6. Verification with the finite element method

Numerical verification is carried out in order to control the compatibility of the crack pattern of the BRC beam with the stress contour that occurs. The numerical method employed is the finite element method, using the Fortran PowerStation 4.0 program. Theoretical analysis to calculate the load that causes the initial crack uses elastic theory (linear analysis) with a transformation section. For linear analysis, the material data included is the elastic modulus (E) and the Poisson ratio (v). The non-linear phase is approached by giving a decrease in the strength of concrete 0.25-0.5 for the calculation of effective stiffness in the plastic area [42]. FEM analysis has not modeled the bond between bamboo reinforcement and concrete, where bamboo and concrete are considered to have the same displacement, with a different modulus of elasticity (E), so that they experience different stress. FEM analysis in this study has not been explained in detail and needs further analysis. In the constitutive relationship of finite element analysis, the problem-solving method has used the theory of plane-stress. Triangle elements are used to model plane-stress elements with two-way primary displacement at each point, so that the element has six degrees of freedom. The discretization of the beam plane was carried out using the triangle element shown in Fig. 23.





The modulus of elasticity (E), for each layer was calculated according to the conditions of the material. The layers consisting of the concrete and the bamboo reinforcement are calculated using the following Eq. (9) [43].

$$E_e = E_b V_b + E_c V_c \tag{9}$$

with E_e = equivalent elasticity modulus of BRC beam, E_b = modulus of elasticity of bamboo reinforcement, E_c = modulus of elasticity of concrete, V_b = relative volume of bamboo reinforcement in the calculated layer, and V_c = relative volume of concrete in the calculated layer. The stress-strain relationship for plane-stress problems has the form of an equation like Eq. (10).

$$\begin{cases} \sigma_x \\ \sigma_y \\ \tau_{xy} \end{cases} = \frac{E}{(1+\nu^2)} \begin{bmatrix} 1 & \nu & 0 \\ \nu & 1 & 0 \\ 0 & 0 & \frac{1-\nu}{2} \end{bmatrix} \begin{cases} \varepsilon_x \\ \varepsilon_y \\ \gamma_{xy} \end{cases}$$
(10)

where E is the modulus of elasticity of the BRC beam and v is Poisson's ratio. And the principal stress in two dimensions is be calculated with Eq. (11).

$$\sigma_{1,2} = \frac{\sigma_x + \sigma_y}{2} \pm \sqrt{\left(\frac{\sigma_x - \sigma_y}{2}\right)^2 + \tau_{xy}^2} = \sigma_{\max}$$
(11)

Fig. 24 shows that stiffness decreases after the initial crack, according to the loading stage of each mesh layer, and this is very influential on the results of the analysis. The average stiffness of the BRC beam was reduced from 26324.76 MPa before cracking to 6581.20 MPa after the collapse [42], while the average value of the stiffness of the SRC beam was reduced from 30334.11 MPa before cracking to 16873.35 MPa after the collapse. Fig. 24 shows that the results of the load-deflection relationship model from the analysis are quite close to the experimental results.



Fig. 24. The behavior of the load-deflection relationship of the BRC beam and the SRC beam using the finite element method

Along with increasing load, deflection and moments will continue to increase. When the crack moment (M_{cr}) is exceeded, the initial crack will occur, especially at the maximum moment. After the initial crack occurs, bond-stress will occur on bamboo reinforcement and concrete. Bond-stress and cracks will continue to propagate at the weak point of the beam section.



Fig. 26. The stress contour of the BRC beam



Fig. 28. The crack pattern of the SRC beam



Fig. 29. Failure of bond-slip of the BRC beam [21]

Fig. 25 and Fig. 26 show the crack pattern of the experimental result BRC beam and the contour stress result from the Surfer 9.8 program simulation. The position of the crack line and crack propagation are in accordance with the tensile stress contours of the simulation results, ie at coordinates 15 to 95. The red represents the maximum tensile stress, and the grayish blue represents maximum compressive stress. After initial cracking in the middle of the span, branching cracks occur in the position of the bamboo reinforcement. New cracks arise and branch upwards, right, and left. However, most additional cracks propagate to the right and left, following the direction of bamboo reinforcement, in accordance with the maximum tensile stress contour resulting from the simulation. At this stage of branching cracks, the hose-clamp serves as a slip barrier and transfers the force to the concrete, as is evidenced by the many upward cracks that occur at the hose-clamp position, and the increasing spread of cracks spread. Documentation of the crack process can be seen by clicking the following link: https://goo.gl/6AVWmP.

The contribution of the hose-clamp to the bond-stress can be seen in the difference between the crack pattern in the results of this study and that of Agarwal's [21] study, as shown in Fig. 25 and Fig. 29. The crack line in the direction of the bamboo reinforcement proves the slip between bamboo reinforcement and concrete. The occurrence of slip proves that the elasticity modulus of bamboo is lower than that of concrete, causing low bond-stress. Therefore, the calculation of the BRC beam cross-sectional capacity must be based on the bamboo reinforcement shear area, not on the tensile strength of the bamboo reinforcement; this is in accordance with Ghavami's [1] research on the stress-strain distribution analysis of bamboo reinforced concrete beams.

Fig. 27 and Fig. 28 show the stress contours of the SRC beam resulting from the simulation in the Surfer 9.8 program and the crack pattern of the experimental result for the SRC beam. The coordinates of the crack pattern and the maximum tensile stress coordinates of the simulation results show suitability, which occurs at coordinates 35 to 75. Patterns of cracks and collapse are flexural cracks and flexural collapse. This proves that the bond strength of steel reinforcement is higher than the bond strength of bamboo reinforcement. After the initial crack occurs, along with increasing load, cracks continue to propagate upwards until collapse occurs.

5. Conclusions

Based on experiment, verification using the finite element method, and evaluation results on bamboo reinforced concrete beams with reinforcement using a hose-clamp, the following conclusions can be drawn:

- Installation of hose-clamps on bamboo reinforcement serves as a shear connector, can increase bond-stress, and reduce the slip between bamboo reinforcement and concrete.
- (2) The BRC beam load-deflection relationship model has a gap that is far enough with the SRC beam load-deflection diagram. The stiffness of the BRC beam is lower than the stiffness of the SRC beam. The principle of the theory of confined concrete and shear reinforcement can be a solution to overcome the low rigidity of the BRC beam.

- (3) The relationship model of bond-stress and slip in a BRC beam is different from the bond-stress and slip relationship model in an SRC beam. The friction bond limit of the BRC beam occurs at $0.2P_{ultimate}$ and the friction bond limit of the SRC beam occurs at $0.4P_{ultimate}$. This difference is due to the stress-strain characteristics and the elastic modulus of the materials from the two different test objects.
- (4) The stress-strain characteristics of the materials, the modulus of elasticity of the materials, and the test method of the specimens are very influential to the relationship model of the bond-stress and slip.

Acknowledgments

The research described in this paper was financially supported by the Domestic Postgraduate Education Scholarship (BPP-DN), at the University of Brawijaya, Malang, Indonesia.

References

- K. Ghavami, Bamboo as reinforcement in structural concrete elements, Cement and Concrete Composites. 27 (2005) 637–649.
- [2] C. Sabnani, M. V Latkar, U. Sharma, Bamboo an alternative building material for modest houses, to increase the stock of affordable housing, for the urban poor living close to bamboo producing regions in India, International Journal of Civil, Environmental, Structural, Construction and Architectural Engineering. 6 (2012) 977–988.
- [3] H. Sakaray, N.V.V.K. Togati, I.V.R. Reddy, Investigation on properties of bamboo as reinforcing material in concrete, International Journal of Engineering Research and Applications. 2 (2012) 77–83.
- [4] P.A. Pratima, M.R. Adit, G.J. Vivek, P.A. Jaymin, M.H. Sunny, Performance Evaluation Of Bamboo As Reinforcement In Design Of Construction Element, International Refereed Journal of Engineering and Science (IRJES). 2 (2013) 55–63.
- [5] P.K. Imbulana, T. Fernandez, P.A.R.P. Jayawardene, T.P. Levangama, Y.K. Perera, H.N.K. Arachchi, R.S. Mallawaarachchi, Bamboo as a Low Cost and Green Alternative for Reinforcement in Light Weight Concrete, in: SAITM Research Symposium on Engineering Advancements 2013 (SAITM RSEA 2013), Sri Lanka, 2013: pp. 166–172.
- [6] N. Anurag, S.B. Arehant, J. Abhishek, K. Apoorv, T. Hirdesh, Replacement of Steel by Bamboo Reinforcement, IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE). 8 (2013) 50–61.
- [7] A. Kaware, U.R. Awari, M.R. Wakchaure, Review of Bamboo as Reinforcement Material in Concrete Structure, International Journal of Innovative Research in Science, Engineering and Technology. 2 (2013) 2461–2464.
- [8] G.M. Oka, A. Triwiyono, A. Awaludin, S. Siswosukarto, Effects of node, internode and height position on the mechanical properties of gigantochloa atroviolacea bamboo, Procedia Engineering. 95 (2014) 31–37.
- [9] I.K. Khan, Performance of Bamboo Reinforced Concrete Beam, International Journal of Science, Environment and Technology. 3 (2014) 836–840.
- [10] S. Pawar, Bamboo in Construction Technology, Advance in Electronic and Electric Engineering. 4 (2014) 347– 352.
- [11] D.D. Tripura, K.D. Singh, Mechanical behavior of rammed earth column : A comparison between unreinforced, steel and bamboo reinforced columns, Materiales de Construcción. 68 (2018) 1–19.
- [12] S. Islam, H.M. Afefy, K. Sennah, H. Azimi, Bond characteristics of straight- and headed-end, ribbed-surface, GFRP bars embedded in high-strength concrete, Construction and Building Materials. 83 (2015) 283–298.
- [13] M.S. Ahmad, Bond in Flexure : A Review of ACI CODE 408R, International Journal of Advanced Technology in Engineering and Science. 4 (2016) 79–84.
- [14] Y. Lee, B. Phares, Bond Strength and Development Length of Galvanized Reinforcing Steel, International Journal of Civil and Structural Engineering Research. 3 (2015) 311–317.
- [15] A.S. Budi, A.P. Rahmadi, E. Rismunarsi, Experimental Study of Flexural Capacity on Bamboo Ori Strip Notched V Reinforced Concrete Beams, in AIP Conf. Proc. 1788 - International Conference on Engineering, Science and Nanotechnology 2016 (ICESNANO 2016), American Institute of Physics, 2016: pp. 030052-1– 030052-7.
- [16] A. Dey, N. Chetia, Experimental study of Bamboo Reinforced Concrete beams having various frictional properties, Materials Today: Proceedings. 5 (2016) 436–444.
- [17] S.M. Dewi, D. Nuralinah, The Recent Research on Bamboo Reinforced Concrete, in MATEC Web of Conferences, EDP Sciences, 2017: p. 2001.
- [18] Muhtar, S.M. Dewi, Wisnumurti, A. Munawir, Bond-slip improvement of bamboo reinforcement in concrete beam using hose clamps, Proceedings The 2nd International Multidisciplinary Conference 2016. (2016) 385–

393.

- [19] Muhtar, S.M. Dewi, Wisnumurti, A. Munawir, The stiffness and cracked pattern of bamboo reinforced concrete beams using a hose clamp, International Journal of Civil Engineering and Technology. 9 (2018).
- [20] S.M. Dewi, D. Nuralinah, A. Munawir, M.N. Wijaya, Crack Behavior Study of Bamboo Reinforced Concrete Beam with Additional Pegs in Reinforcing, 9 (2018) 1632–1640.
- [21] A. Agarwal, B. Nanda, D. Maity, Experimental investigation on chemically treated bamboo reinforced concrete beams and columns, Construction and Building Materials. 71 (2014) 610–617.
- [22] G.C.S. Ferreira, A.L. Beraldo, A.L.J. Moreno, A.O.B. Da Silva, Flexural and shear behavior of concrete beams reinforced with bamboo, International Journal of Sustainable Materials and Structural Systems. 2 (2016) 335.
- [23] S. Leelatanon, S. Srivaro, N. Matan, Compressive strength and ductility of short concrete columns reinforced by bamboo, Songklanakarin Journal of Science and Technology. 32 (2010) 419–424.
- [24] N.B. Siddhpura, D.B. Shah, J. V Kapadia, C.S. Agrawal, J.K. Sevalia, Experimental study on a flexural element using bamboo as reinforcement, International Journal of Current Engineering and Technology. 3 (2013) 476– 483.
- [25] Nindyawati, S.M. Dewi, A. Soehardjono, The Comparison Between Pull-Out Test And Beam Bending Test To The Bond Strength Of Bamboo Reinforcement In Light Weight Concrete, International Journal of Engineering Research and Applications (IJERA). 3 (2013) 1497–1500.
- [26] D. Bhonde, P.B. Nagarnaik, D.K. Parbat, U.P. Waghe, Experimental Analysis of Bending Stresses in Bamboo Reinforced Concrete Beam, in Proceedings of 3rd International Conference on Recent Trends in Engineering & Technology (ICRTET'2014), Elsevier Ltd., Nagpur, India, 2014: pp. 1–5.
- [27] E. Ikponmwosa, F. Falade, C. Fapohunda, J. Okosun, Flexural Performance of Bamboo Reinforced Foamed Aerated Concrete Beams With and Without Compression Reinforcement, International Journal of Scientific & Engineering Research. 5 (2014) 271–278.
- [28] P. V Kumar, V. Vasugi, Study on Mechanical Strength of Bamboo Reinforced Concrete Beams, International Journal of Advances in Science Engineering and Technology. 2 (2014) 103–105.
- [29] K. Terai, Masakazu & Minami, Research and Development on Bamboo Reinforced Concrete Structure, World Conferences on Earthquake Engineering. (2012) 1–10.
- [30] A. Javadian, M. Wielopolski, I.F.C. Smith, D.E. Hebel, Bond-behavior study of newly developed bamboocomposite reinforcement in concrete, Construction and Building Materials. 122 (2016) 110–117.
- [31] V. Puri, P. Chakrabortty, S. Anand, S. Majumdar, Bamboo reinforced prefabricated wall panels for low-cost housing, Journal of Building Engineering. 9 (2017) 52–59. doi:10.1016/j.jobe.2016.11.010.
- [32] F. Falade, G.L. Oyekan, Bond Strength of Reinforced Laterized Concrete Bond Strength of Reinforced Laterized Concrete Beams, in 31st Conference on Our World In Concrete & Structures, CI-Premier PTE LTD, Singapore, 2006.
- [33] A.M. Diab, H.E. Elyamany, M.A. Hussein, H.M. Al Ashy, Bond behavior and assessment of design ultimate bond stress of normal and high strength concrete, Alexandria Engineering Journal. 53 (2014) 355–371.
- [34] R. Park, T. Paulay, Reinforced Concrete Structures, in John Wiley & Sons, New York, 1975: pp. 1–769.
- [35] M.M. Rahman, M.H. Rashid, M.A. Hossain, M.T. Hasan, M.K. Hasan, Performance evaluation of bamboo reinforced concrete beam, International Journal of Engineering & Technology IJET-IJENS. 11 (2011) 113–118.
- [36] ASTM C 09, Standard Test Method for Flexural Strength of Concrete (Using Simple Beam with Third-Point Loading), ASTM International, West Conshohocken, 2002.
- [37] ASTM E2126-09, Standard Test Methods for Cyclic (Reversed) Load Test for Shear Resistance of Vertical Elements of the Lateral Force Resisting Systems for Buildings1, ASTM International, West Conshohocken, 2009.
- [38] ASTM C 39, Standard Test Method for Compressive Strength of Cylindrical Concrete Specimens, ASTM International, West Conshohocken, 2003.
- [39] S. Nathan, Application of Bamboo for Flexural and Shear Reinforcement in Concrete Beams, Clemson University, 2014.
- [40] L. Khare, Performance Evaluation of Bamboo Reinforced Concrete Beams, 2005.
- [41] R. Piyasena, Crack Spacing, Crack Width and Tension Stiffening Effect in Reinforced Concrete Beams and One-Way Slabs, Griffith University, 2002. https://researchrepository.griffith.edu.au/bitstream/handle/10072/366060/Piyasena 2003 01Thesis.pdf?sequence=1.
- [42] ACI Committee 318, Building Code Requirements for Structural Concrete (ACI 318M-14), 2014.
- [43] C. Avram, I. Facaoaru, I. Filimon, O. Mirsu, I. Tertea, Concrete strength and strain, Developments in Civil Engineering 3, 1981.

Highlights

The model of strengthening of bamboo reinforcement on bamboo reinforced concrete using a hose-clamp

The model of the load-deflection relationship on bamboo reinforced concrete beam

The relationship models of bond-stress and slip on bamboo reinforced concrete beam